



### Main

Range of product	Multi9
Product or Component Type	Connector
Accessory / separate part categor	Connection accessory
Quantity per Set	Set of 4

### Complementary

Line Rated Current	63 A
[Ui] Rated Insulation Voltage	1000 V
Connection pitch	0.7 in (18 mm)
Standards	UL 486E
Product certifications	CURus[RETURN]IEC
Color	White RAL 9001)
Connections - terminals	Screw terminal top connector 0.009...0.05 in <sup>2</sup> (6...35 mm <sup>2</sup> ) rigid Screw terminal top connector 0.009...0.05 in <sup>2</sup> (6...35 mm <sup>2</sup> ) flexible
Tightening torque	31.0 lbf.in (3.5 N.m)
Range compatibility	Multi9 Multi9 C60 C60BP comb busbar

### Ordering and shipping details

Category	US10DE200949
Discount Schedule	0DE2
GTIN	3606481192936
Returnability	Yes
Country of origin	DE

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.102 in (2.800 cm)
Package 1 Width	3.701 in (9.400 cm)
Package 1 Length	5.315 in (13.500 cm)
Package 1 Weight	5.291 oz (150.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	25
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	9.202 lb(US) (4.174 kg)

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.