

Product data sheet

Specifications



split core current transformer,
PowerLogic UL2808 CT, 100A,
0.333V output, 16mm diameter, 6ft
lead

METSECTLV1010U

Product availability: Stock - Normally stocked in distribution facility

Main

Range	PowerLogic
Device short name	LVCT
Product or Component Type	Current transformer
Output voltage	0.333 V
Electrical connection	Flying lead 6 ft (1.8 m) AWG 16) 600 V
Product destination	iEM3000 EM3500 EM4200 EM4900
Current transformer type	Split core
Line Rated Current	100 A
Network Frequency	50 Hz 60 Hz

Complementary

Range compatibility	PowerLogic PowerLogic EM3500 EM3502 energy meter PowerLogic PowerLogic EM3500 EM3550 energy meter PowerLogic PowerLogic EM3500 EM3555 energy meter PowerLogic PowerLogic EM3500 EM3560 energy meter PowerLogic PowerLogic EM3500 EM3561 energy meter PowerLogic PowerLogic EM3570 EM3570 energy meter PowerLogic PowerLogic EM4200 EM4235 energy meter PowerLogic PowerLogic EM4200 EM4236 energy meter PowerLogic PowerLogic EM4900 EM4904 multi-circuit energy meter PowerLogic PowerLogic EM4900 EM4908 multi-circuit energy meter PowerLogic PowerLogic EM4900 EM4914 multi-circuit energy meter PowerLogic PowerLogic EM4900 EM4928 multi-circuit energy meter Acti 9 Acti9 iEM3000 iEM3455 energy meter Acti 9 Acti9 iEM3000 iEM3465 energy meter
Measurement accuracy	1 %

Environment

Relative humidity	0...95 %
Ambient Air Temperature for Operation	32...158 °F (0...70 °C)
Ambient Air Temperature for Storage	-40...221 °F (-40...105 °C)
Width	Internal: 0.6 in (16 mm) Total: 1.6 in (41 mm)
Depth	1.2 in (31 mm)
Height	Internal: 0.6 in (16 mm) Total: 2.09 in (53 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	US10PL109795
Discount Schedule	0PL1
GTIN	3606487001881
Returnability	Yes
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.047 in (5.200 cm)
Package 1 Width	2.756 in (7.000 cm)
Package 1 Length	3.937 in (10.000 cm)
Package weight(Lbs)	6.631 oz (188.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	24
Package 2 Height	5.315 in (13.500 cm)
Package 2 Width	12.598 in (32.000 cm)
Package 2 Length	12.992 in (33.000 cm)
Package 2 Weight	10.803 lb(US) (4.900 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	24
Package 3 Height	11.024 in (28.000 cm)
Package 3 Width	31.496 in (80.000 cm)
Package 3 Length	23.622 in (60.000 cm)
Package 3 Weight	26.455 lb(US) (12.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	17 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	13 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	80
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.