METSECTSP5A2020U

Split core current transformer, PowerLogic UL2808 CT, 200A, 5A output



Main

Range	PowerLogic	
Product or Component Type	Current transformer	
Accessory / separate part categor	Measurement accessory	

Complementary

Range compatibility	PowerLogic PowerLogic PM5000 power meter PowerLogic PowerLogic PM3000 power meter Acti 9 Acti9 iEM3000 energy meter EasyLogic EasyLogic PM2100 power meter EasyLogic EasyLogic PM2200 power meter	
Current transformer type	Split core	
Primary operational current	200 A	
Secondary current	5 A	
Network type	AC	
Network Frequency	50 Hz 60 Hz	
Current transformer ratio	200/5	
Electrical connection	8 ft (2.4 m) AWG 16 flying lead	
Insulation	Basic insulation 600 V AC Reinforced insulation 300 V AC	
Measurement accuracy	1 %	
Mounting Location	Indoor use only	
Width	Internal: 1.4 in (35.6 mm) Total: 4.12 in (104.65 mm)	
Depth	1.12 in (28.45 mm)	
Height	Internal: 1.4 in (35.6 mm) Total: 3.25 in (82.55 mm)	
Net Weight	18.4 oz (521 g)	

Environment

Relative humidity	095 % non condensing	
Installation category	III	
Pollution degree	2	
Ambient air temperature for operation	5.0000000000140.0000000000 °F (-1560 °C)	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Operating altitude	<= 6561.68 ft (2000 m)	
Standards	UL 2808	
Product certifications	UL	

Ordering and shipping details

Category	US10PL109661
Discount Schedule	0PL1
GTIN	3606489703547
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.1 in (10.5 cm)	
Package 1 Width	8.9 in (22.7 cm)	
Package 1 Length	10.3 in (26.2 cm)	
Package 1 Weight	28.3 oz (802.9 g)	

Offer Sustainability

REACh Declaration
Yes
Compliant EPEU RoHS Declaration
☑ China RoHS Declaration
₫Yes
The product must be disposed on European Union markets following specific
_