

power meter PowerLogic PM5562, 2 ethernet, up to 63th Harmonic, 1,1MB 4DI/2DO 52 alarms, RMICAN lock

METSEPM5562

## Main

Range	PowerLogic	
Product name	PowerLogic PM5000	
Device short name	PM5562	
Product or component type	Power meter	

# Complementary

Complementary		
Power quality analysis	up to the 63rd harmonic	
Metering type	Measured neutral current	
	Calculated ground current	
Device application	Gateway	
	WAGES metering	
	Power monitoring	
	Multi-tariff	
Type of measurement	Current	
	Voltage	
	Frequency	
	Power factor	
	Energy	
	Active and reactive power	
supply voltage	100300 V DC	
	90528 V AC 4565 Hz	
Network frequency	60 Hz	
	50 Hz	
[In] rated current	1A	
	5 A	
type of network	3P + N	
	3P	
	1P + N	
Maximum power consumption in VA	10 VA at 480 V	
Ride-through time	35 ms 120 V AC typical	
	129 ms 230 V AC typical	
Display type	Backlit LCD	
Display resolution	128 x 128 pixels	
Sampling rate	128 samples/cycle	
Measurement current	5010000 mA	
Analogue input type	Voltage (impedance 5 MOhm)	
	Current (impedance <= 0.3 mOhm)	
Measurement voltage	20400 V AC 4565 Hz between phase and neutral	
	20828 V AC 4565 Hz between phases	

Frequency measurement range	4565 Hz	
Number of inputs	4 digital	
Measurement accuracy	Apparent power +/- 0.5 % Frequency +/- 0.05 % Active energy +/- 0.2 % Reactive energy +/- 1 % Active power +/- 0.2 % Voltage +/- 0.1 % Power factor +/- 0.005 Current +/- 0.15 %	
Accuracy class	Class 0.2S active energy conforming to IEC 62053-22	
Number of outputs	2 digital	
Information displayed	Tariff (8)	
Communication port protocol	Modbus RTU and ASCII at 9.6, 19.2 and 38.4 kbauds even/odd or none - 2 wires, insulation 2500 V JBUS Modbus TCP/IP at 10/100 Mbit/s, insulation 2500 V Ethernet Modbus TCP/IP daisy chain BACnet IP	
Communication port support	RS485 ETHERNET	
Communication gateway	Ethernet/serial	
Data recording	Event logs Maintenance logs Min/max of instantaneous values Data logs Alarm logs Time stamping	
Memory capacity	1.1 MB	
Web services	Alarm notification by e-mail Diagnostic via predefined web pages Web server Real time viewing of data	
Ethernet service	SNTP client SNMP-Traps	
Tamperproof of settings	RMICAN protected Hardware lock by jumper	
Connections - terminals	Voltage circuit: screw terminal block4 Control circuit: screw terminal block2 Current transformer: screw terminal block6 RS485 link: screw terminal block4 Digital input: screw terminal block8 Digital output: screw terminal block4 Ethernet network: RJ45 connector2	
Mounting mode	Flush-mounted	
Mounting support	Framework	
Standards	EN 50470-3 IEC 61557-12:2015 IEC 62053-22:2020 IEC 62053-24 IEC 60529 EN 50470-1 UL 61010-1 IEC 62053-23:2020 IEC 62052-11:2020 IEC 62052-31:2015	
Product certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1	
	BTL	

Depth	72 mm
Height	96 mm
Net weight	450 g

# **Environment**

Electromagnetic compatibility	Limits for harmonic current emissions class A conforming to IEC 61000-3-2 Conducted RF disturbances level 3 conforming to IEC 61000-4-6 Magnetic field at power frequency level 4 conforming to IEC 61000-4-8 Conducted and radiated emissions class B conforming to EN 55022 Limitation of voltage changes, voltage fluctuations and flicker in low-voltage conforming to IEC 61000-3-3 Electrostatic discharge - test level: 8 kV level 4 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 Surge immunity test level 4 conforming to IEC 61000-4-5 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11	
IP degree of protection	IP54 display: conforming to IEC 60529 IP30 rear: conforming to IEC 60529	
Relative humidity	595 % at 50 °C non-condensing	
Pollution degree	2	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4085 °C	
Operating altitude	3000 m	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.21 cm
Package 1 Width	13.21 cm
Package 1 Length	13.21 cm
Package 1 Weight	0.64 kg
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	6.2 kg
Unit Type of Package 3	P06
Number of Units in Package 3	96
Package 3 Height	105 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	49.5 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	326
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	C32c2d48-7f52-422d-8a44-67c4f7d4c788
REACh Regulation	REACh Declaration
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

### Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins