

Product data sheet

Specifications



PowerLogic Remote display, color touchscreen, 192 x 192 mm for ION9200

METSERD192

Main

| | |
|---------------------------|------------------------------------|
| Range | PowerLogic |
| Product or component type | Remote display |
| Device application | Human-machine dialogue application |
| Range compatibility | PowerLogic PowerLogic ION9000 |
| Display type | LCD touch screen |

Complementary

| | |
|---------------------------|---------------------------------------------------------------------------------------------------------------------|
| Display colour | Color |
| Display resolution | 800 x 480 pixels |
| Display size | 7 inch |
| Information displayed | Energy consumption Voltage Power Harmonic distortion Frequency Current System alarm I/O status |
| Messages display capacity | Graphic objects (bargraph, button, light...) |
| Local signalling | Status: LED (green) Alarm: LED (red) |
| Control type | 1 x push-button Touch screen |
| Connector type | RJ45 |
| Provided equipment | Mounting hardware |
| Mounting mode | Flush-mounted |
| Mounting support | Framework remote display |
| Width | 197 mm |
| Height | 175 mm |
| Projecting depth | 27.5 mm |
| Net weight | 300 g |

Environment

| | |
|-------------------------|------------------------------|
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK08 |
| Relative humidity | 5...95 % |

| | |
|----------------------------------------------|-------------|
| Operating altitude | 0...3000 m |
| Ambient air temperature for operation | -25...60 °C |
| Ambient air temperature for storage | -40...85 °C |
| Product certifications | IEC IEEE |

Packing Units

| | |
|-------------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 14.0 cm |
| Package 1 Width | 24.0 cm |
| Package 1 Length | 26.0 cm |
| Package 1 Weight | 1.6 kg |



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 661

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 593f15dc-c512-4cf6-ac2d-78a614f80e12

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins