



Main

Range Compatibility	PacDrive 3
Device short name	MH3
Product or Component Type	AC servo motors

Complementary

Maximum mechanical speed	8000 rpm
[Us] rated supply voltage	115...480 V
Phase	Three phase
Continuous stall current	1.78 A
Continuous stall torque	12.4 lbf.in (1.4 N.m), 115...480 V, three phase
Continuous power	930 W
Peak stall torque	37.2 lbf.in (4.2 N.m), 115...480 V, three phase
Nominal output power	0.18 W, 115 V 0.42 W, 230 V 0.75 W, 400 V 0.93 W, 480 V
Nominal torque	12.21 Lbf.in (1.38 N.m) LXM52 1.75 mA, 115 V, 1 phase 11.86 Lbf.in (1.34 N.m) LXM52 1.75 mA, 230 V, 1 phase 11.5 Lbf.in (1.3 N.m) LXM52 1.72 mA, 400 V, 3 phase 11.24 Lbf.in (1.27 N.m) LXM52 1.7 mA, 480 V, 3 phase 12.21 Lbf.in (1.38 N.m) LXM62 1.75 mA, 115 V, 1 phase 11.86 Lbf.in (1.34 N.m) LXM62 1.75 mA, 230 V, 1 phase 11.5 Lbf.in (1.3 N.m) LXM62 1.72 mA, 400 V, 3 phase 11.24 Lbf.in (1.27 N.m) LXM62 1.7 mA, 480 V, 3 phase
Nominal speed	1250 rpm LXM52 1.75 mA, 115 V, 1 phase 3000 rpm LXM52 1.75 mA, 230 V, 1 phase 5500 rpm LXM52 1.72 mA, 400 V, 3 phase 7000 rpm LXM52 1.7 mA, 480 V, 3 phase 1250 rpm LXM62 1.75 mA, 115 V, 1 phase 3000 rpm LXM62 1.75 mA, 230 V, 1 phase 5500 rpm LXM62 1.72 mA, 400 V, 3 phase 7000 rpm LXM62 1.7 mA, 480 V, 3 phase
Maximum current Irms	5.97 A
Shaft end	Smooth shaft
Second shaft	Without second shaft end
Shaft diameter	0.4 in (11 mm)
Shaft length	0.9 in (23 mm)
IP Degree of Protection	IP65 standard
Encoder type	Single turn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	Without
Mounting Support	International standard flange
Motor flange size	2.8 in (70 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Electrical Connection	Rotatable right-angled connectors
Torque constant	0.79 N.m/A 248 °F (120 °C)
Back emf constant	50.72 V/krpm
Number of motor poles	10
Rotor inertia	0.59 kg.cm ²
Stator resistance	8.28 Ohm
Stator inductance	23.4 mH
Stator electrical time constant	2.8 ms
Maximum radial force Fr	660 N 1000 rpm 520 N 2000 rpm 460 N 3000 rpm 410 N 4000 rpm 380 N 5000 rpm 360 N 6000 rpm
Type of cooling	Natural convection
Length	4.8 in (122 mm)
Centring collar diameter	2.4 in (60 mm)
Centring collar depth	0.10 in (2.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.2 in (5.5 mm)
Circle diameter of the mounting holes	3.2 in (82 mm)
Net Weight	3.5 lb(US) (1.6 kg)

Ordering and shipping details

Category	US1PC5218359
Discount Schedule	PC52
GTIN	3606485394787
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 in (11.5 cm)
Package 1 Width	7.5 in (19.0 cm)
Package 1 Length	15.6 in (39.5 cm)
Package 1 Weight	4.890 lb(US) (2.218 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes