


# Product data sheet

Specifications



## Cable entry membrane, PanelSeT, PanelSeT, type FL21 with 35 entrances IP66

NSYAECPFLT35

### Overview

**Lead time** Usually Ships within 4 Weeks

### Main

<b>Range</b>	PanelSeT
<b>Product or component type</b>	Cable entry membrane
<b>Accessory / separate part category</b>	Cable management accessory
<b>Device application</b>	Multi-purpose
<b>Range compatibility</b>	PanelSeT S3D compact enclosure PanelSeT CRN compact enclosure PanelSeT SF suitable enclosure
<b>Device composition</b>	1 membrane 1 fixing elements
<b>Quantity per set</b>	Set of 1

### Complementary

<b>Mounting support</b>	Cable gland plate
<b>Material</b>	TPE (thermoplastic elastomer)
<b>Fixing mode</b>	By fixing element
<b>Total cable entry number</b>	35
<b>Cable entry number</b>	14 x 8...12 mm 16 x 10...14 mm 2 x 12...18 mm 1 x 17...32 mm 2 x 6...10 mm
<b>Height</b>	40 mm
<b>Width</b>	External: 214 mm Fixing center: 194 mm
<b>Depth</b>	Fixing center : 62 mm External : 88 mm
<b>Colour</b>	Grey (RAL 7035)
<b>Net weight</b>	0.34 kg

### Environment

<b>IP degree of protection</b>	IP66
<b>Flame retardance</b>	V0 conforming to UL 94
<b>Ambient air temperature for operation</b>	-40...100 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Environmental characteristic</b>	Oil resistant conforming to UL 157 FIMKO UV resistant Weatherproof Fire resistance conforming to UL 94 V0
-------------------------------------	--

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	3.000 cm
<b>Package 1 Width</b>	14.000 cm
<b>Package 1 Length</b>	25.500 cm
<b>Package 1 Weight</b>	324.000 g
<b>Unit Type of Package 2</b>	CAR
<b>Number of Units in Package 2</b>	20
<b>Package 2 Height</b>	20.000 cm
<b>Package 2 Width</b>	31.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	6.730 kg
<b>Unit Type of Package 3</b>	PAM
<b>Number of Units in Package 3</b>	800
<b>Package 3 Height</b>	93.000 cm
<b>Package 3 Width</b>	100.000 cm
<b>Package 3 Length</b>	120.000 cm
<b>Package 3 Weight</b>	284.000 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation

[REACH Declaration](#)

## Use Again

### Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No