

# Product data sheet

Specifications



## Climasys CC - Electronical thermostat 200..240V - range of temperature -40â€¦80Â°C

NSYCCOTH230VID

**Product availability: Non-Stock - Not normally stocked in distribution facility**

### Main

Range	ClimaSys
Product name	ClimaSys CC
Product or Component Type	Electronical thermostat
Temperature setting range	-40...176 °F (-40...80 °C)
Display Type	OLED screen
Information Displayed	Temperature in °F Temperature in °C

### Complementary

Input voltage	200...240 V AC
Sensor Type	Optional NTC external sensor
Maximum switching capacity	4 A 230 V AC
Electrical connection	10 terminals 2.5 mm <sup>2</sup>
Mounting Mode	Clipped By screws
Height	External: 3.3 in (85 mm)
Width	External: 2.2 in (56 mm)
Depth	External : 1.7 in (44 mm)
Mounting Location	Cross rails On mounting plate Spacial upright 35 mm DIN rail
Ambient Air Temperature for Operation	-40...176 °F (-40...80 °C)
Hysteresis	2 K programmed value
Number of outputs	2 ventilation/heating function
Material	PC
Color	Light gray
Flame retardance	Self-extinguishing conforming to UL94 (material V0)
Product Certifications	UR

### Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480152627

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Returnability</b>	No
----------------------	----

---

<b>Country of origin</b>	CN
--------------------------	----

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Nbr. of units in pkg.</b>	1
------------------------------	---

---

<b>Package 1 Height</b>	3.346 in (8.500 cm)
-------------------------	---------------------

---

<b>Package 1 Width</b>	2.953 in (7.500 cm)
------------------------	---------------------

---

<b>Package 1 Length</b>	2.165 in (5.500 cm)
-------------------------	---------------------

---

<b>Package weight(Lbs)</b>	2.469 oz (70.000 g)
----------------------------	---------------------

---

## Contractual warranty

---

<b>Warranty</b>	18 months
-----------------	-----------

---

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

SCIP Number

3452f1a3-f13d-4adf-84ba-2572bcc8e35c

REACH Regulation

[REACH Declaration](#)

## Use Again

### Repack and remanufacture


Circularity Profile

No need of specific recycling operations

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.