

Product data sheet

Specifications



Climasys CC - Electronical thermostat 9...30V - range of temperature -40â€¦80Â°C

NSYCCOTH30VID

Main

Range	ClimaSys
Product name	ClimaSys CC
Product or component type	Electronical thermostat
Temperature setting range	-40...80 °C
Display type	OLED screen
Information displayed	Temperature in °F Temperature in °C

Complementary

Input voltage	9...30 V AC/DC
Sensor type	Optional NTC external sensor
Maximum switching capacity	4 A 30 V AC/DC
Electrical connection	10 terminals, clamping capacity: 2.5 mm²
Mounting mode	By screws Clipped
Height	External: 85 mm
Width	External: 56 mm
Depth	External : 44 mm
Mounting location	On mounting plate Cross rails 35 mm DIN rail Spacial upright
Ambient air temperature for operation	-40...80 °C
Hysteresis	2 K programmed value
Number of outputs	2 ventilation/heating function
Material	PC
Colour	Light grey
Flame retardance	Self-extinguishing conforming to UL94 (material V0)
Product certifications	UR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	7.500 cm
Package 1 Length	8.500 cm
Package 1 Weight	138.000 g

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	3452f1a3-f13d-4adf-84ba-2572bcc8e35c
REACH Regulation	REACH Declaration

Use Again

Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins