

Product data sheet

Specifications



ClimaSys PTC heating resistance 350-550W, 120V insulate thermoventilator

NSYCRP1W120VTVC

Main

Range	ClimaSys
Product name	ClimaSys CR
Product or component type	Resistance heater with fan and thermostat
Power range	400...550 W
Input voltage	120 V AC 50/60 Hz
Electrical connection	2 screw terminals 2.5 mm ²

Complementary

Operating position	Vertical
Ambient air temperature for operation	-40...70 °C
Temperature setting range	0...60 °C
IP degree of protection	IP20
Product certifications	UL VDE
Height	220 mm
Width	150 mm
Depth	150 mm
Condition of use	Electrical protection is needed Heaters must be installed with a thermal controller Air sealed enclosure
fixing mode	By clips
Mounting support	35 mm DIN rail

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.000 cm
Package 1 Width	15.000 cm
Package 1 Length	15.000 cm
Package 1 Weight	1.020 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	32.000 cm

Package 2 Width	40.000 cm
Package 2 Length	59.000 cm
Package 2 Weight	10.820 kg
Unit Type of Package 3	P12
Number of Units in Package 3	80
Package 3 Height	81.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	101.800 kg

Contractual warranty

Warranty	18 months
----------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

60bb7229-9ac3-41cb-896e-a93aa448ebf8

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins