

# Product data sheet

Specifications



## ClimaSys forced vent. IP54, 165m<sup>3</sup>/h, 115V, with outlet grille and filter G2

NSYCVF165M115PF

**Product availability: Stock - Normally stocked in distribution facility**

### Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 43589.2 Gal/hr(US) (165 m <sup>3</sup> /h) at 50 Hz Free flow rate with standard filter: 50986.1 Gal/hr(US) (193 m <sup>3</sup> /h) at 60 Hz
[Us] rated supply voltage	75...126 V
Input voltage	115 V 50/60 Hz
Certification	CSA

### Complementary

Absorbed power	15.5 W 50 Hz 14.4 W 60 Hz
Line Rated Current	0.2 A 50 Hz 0.18 A 60 Hz
Noise level < at	50...51 dB
Bearing type	Ball
Height	External: 10.6 in (268 mm)
Width	External: 9.8 in (248 mm)
Depth	External : 4.09 in (104 mm)
Cut-out dimensions	223 x 223 mm
Net Weight	2.51 lb(US) (1.14 kg)
Material	Outlet grille injected thermoplastic (ASA PC)
color	Outlet grille Gray RAL 7035)
Ambient Air Temperature for Operation	-4...140 °F (-20...60 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Maximum pressure	50 Pa flow rate 0 m <sup>3</sup> /h
Connections - Terminals	Faston connector
IP degree of protection	IP54
Device composition	1 axial motor 2 protective grille on the front and rear surfaces 1 filter front of axial motor 1 outlet grille front 1 cut-out template 1 power cord

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Condition of use</b>	<p>Outside temperature must be 5 °C lower than inside temperature</p> <p>Filter must be cleaned and replaced regularly</p> <p>Overfrequent filter replacement should be avoided</p> <p>Flow rates depends on the work point, see ProClima software</p> <p>Surrounding environment must be relatively clean</p>
-------------------------	--

## Ordering and shipping details

<b>Category</b>	US10ES180036
<b>Discount Schedule</b>	0ES1
<b>GTIN</b>	3606480151255
<b>Returnability</b>	Yes
<b>Country of origin</b>	FR

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	7.087 in (18.000 cm)
<b>Package 1 Width</b>	9.843 in (25.000 cm)
<b>Package 1 Length</b>	10.630 in (27.000 cm)
<b>Package weight(Lbs)</b>	3.086 lb(US) (1.400 kg)
<b>Unit Type of Package 2</b>	CAR
<b>Number of Units in Package 2</b>	4
<b>Package 2 Height</b>	10.039 in (25.500 cm)
<b>Package 2 Width</b>	15.354 in (39.000 cm)
<b>Package 2 Length</b>	23.031 in (58.500 cm)
<b>Package 2 Weight</b>	15.256 lb(US) (6.920 kg)
<b>Unit Type of Package 3</b>	P12
<b>Number of Units in Package 3</b>	64
<b>Package 3 Height</b>	48.819 in (124.000 cm)
<b>Package 3 Width</b>	31.496 in (80.000 cm)
<b>Package 3 Length</b>	47.244 in (120.000 cm)
<b>Package 3 Weight</b>	264.555 lb(US) (120.000 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

61d9d3f3-5a49-48f8-8056-1a5ad0ad4c76

REACH Regulation

[REACH Declaration](#)

## Use Again

### Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.