

Product data sheet

Specifications



ClimaSys forced vent. IP54, 38m³/h, 115V, with outlet grille and filter G2

NSYCVF38M115PF

Product availability: Stock - Normally stocked in distribution facility

Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 10038.7 Gal/hr(US) (38 m ³ /h) at 50 Hz Free flow rate with standard filter: 10302.9 Gal/hr(US) (39 m ³ /h) at 60 Hz
[Us] rated supply voltage	75...125 V
Input voltage	115 V 50/60 Hz

Complementary

Absorbed power	3.3 W 50 Hz 3.5 W 60 Hz
Line Rated Current	0.16 A 50 Hz 0.16 A 60 Hz
Noise level < at	40...41 dB
Bearing type	Ball
Height	External: 5.4 in (137 mm)
Width	External: 4.6 in (117 mm)
Depth	External : 1.9 in (49 mm)
Cut-out dimensions	92 x 92 mm
Net Weight	0.49 lb(US) (0.22 kg)
Material	Outlet grille injected thermoplastic (ASA PC)
color	Outlet grille Gray RAL 7035)
Ambient Air Temperature for Operation	14...158 °F (-10...70 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Maximum pressure	29 Pa flow rate 0 m ³ /h
Connections - Terminals	Cable
IP degree of protection	IP54
Device composition	1 axial motor 2 protective grille on the front and rear surfaces 1 filter front of axial motor 1 outlet grille front 1 cut-out template

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Condition of use	Outside temperature must be 5 °C lower than inside temperature Flow rates depends on the work point, see ProClima software Overfrequent filter replacement should be avoided Surrounding environment must be relatively clean Filter must be cleaned and replaced regularly
-------------------------	---

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480151170
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.953 in (7.500 cm)
Package 1 Width	4.921 in (12.500 cm)
Package 1 Length	5.709 in (14.500 cm)
Package weight(Lbs)	10.582 oz (300.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	34
Package 2 Height	23.622 in (60.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	10.827 in (27.500 cm)
Package 2 Weight	23.501 lb(US) (10.660 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	340
Package 3 Height	31.496 in (80.000 cm)
Package 3 Width	39.370 in (100.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	282.192 lb(US) (128.000 kg)

Contractual warranty

Warranty	18 months
-----------------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 3

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 61d9d3f3-5a49-48f8-8056-1a5ad0ad4c76

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.