

# Product data sheet

## Characteristics

# NSYEBAD12614

Power distribution block, Linergy, enclosed, 1 line, 4 load, 200A Cu, 600V, Cu lug, rail mount



### Main

Range of Product	NSYEB
Product or Component Type	Power Distribution Block

### Complementary

[Ue] rated operational voltage	600 V AC/DC
Line Rated Current	200 A copper
Mounting Support	35 mm DIN rail
Electrical connection	Tin plated copper lugs
Number of terminals	1 line 4 load
Number of cables	Line 1, AWG 14...AWG 3/0, copper Load 4, AWG 14...AWG 2, copper
Short-circuit current	100 kA
Material	Thermoplastic: block
Colour of enclosure	Grey
Wire stripping length	Load: 0.69 in (17.53 mm) for bottom connection Line: 0.88 in (22.35 mm) Load: 0.69 in (17.53 mm) for top connection
Connections - terminals	Line lug 180 lbf.in (20.3 N.m) AWG 8...AWG 3/0 copper Line lug 50 lbf.in (5.6 N.m) AWG 14...AWG 10 copper Load lug 50 lbf.in (5.6 N.m) AWG 8...AWG 2 copper Load lug 40 lbf.in (4.5 N.m) AWG 14...AWG 10 copper
Height	3.61 in (91.69 mm)
Tightening torque	Line 180 lb.in, AWG 8...AWG 3/0, copper Line 50 lb.in, AWG 14...AWG 10, copper Load 50 lb.in, AWG 8...AWG 2, copper Load 40 lb.in, AWG 14...AWG 10, copper
Width	1.21 in (30.73 mm)
Depth	2.71 in (68.83 mm)

### Environment

Product Certifications	CE[RETURN]JUL listed file E323110 CCN QPQS[RETURN]CSA file 70361 class 6228 01
Dielectric strength	1000 V 0.1 in <sup>2</sup> (70 mm <sup>2</sup> ) IEC 60947-7-1
Ambient Air Temperature for Operation	-40...125 °C (-40...257 °F)

### Ordering and shipping details

Category	US10CP121713
Discount Schedule	OCP1
GTIN	785901500186
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.700 in (6.858 cm)
Package 1 Width	1.300 in (3.302 cm)
Package 1 Length	3.700 in (9.398 cm)
Package 1 Weight	8.64 oz (244.94 g)

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free product