

Product data sheet

Specifications

Cost-effective LED Lamps - 120/230 V AC - 5W



NSYLAMT5LD1

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or Component Type	Lamp
Device Application	Multi-purpose
Device composition	1 lamp 1 fixing elements 2 cable
Power factor	0.9

Complementary

Outlet standard deviation	Without socket
Rated lamp wattage	5 W
[Ue] rated operational voltage	120/230 V AC 50/60 Hz
Bulb base	Integral LED
Bulb type	LED
Control Type	Built-it switch
Luminous flux	500 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 9.8 ft (3 m) supplied Cable quick connector 3.3 ft (1 m) supplied
Mounting Support	Metal parts Cross rails
Fixing Mode	Magnetic fixing Screws
Range compatibility	Spacial PanelSeT
Length	12.2 in (310 mm)
Height	1.2 in (30.5 mm)
color	Aluminum

Environment

IP degree of protection	IP20 conforming to IEC 60529
Electrical Insulation Class	Class I

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	IEC 60598
Ambient air temperature for operation	14...140 °F (-10...60 °C)
Ambient Air Temperature for Storage	3...149 °F (-16...65 °C)

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606481190369
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.756 in (7.000 cm)
Package 1 Width	3.150 in (8.000 cm)
Package 1 Length	13.780 in (35.000 cm)
Package weight(Lbs)	20.459 oz (580.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	16.535 in (42.000 cm)
Package 2 Width	14.173 in (36.000 cm)
Package 2 Length	11.024 in (28.000 cm)
Package 2 Weight	25.574 lb(US) (11.600 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	1200
Package 3 Height	78.740 in (200.000 cm)
Package 3 Width	39.370 in (100.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	1565.283 lb(US) (710.000 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	58
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration

Use Again

Repack and remanufacture	
Recyclability potential, in %	36
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

