

# Product data sheet

Specifications



## KIT FLUSH-MOUNTING POUR ATV T3

NSYPTDS3

**Product availability: Stock - Normally stocked in distribution facility**

### Main

Range	PanelSeT
Product or Component Type	Drive flush mounting kit
accessory category	Mounting and fixing accessory
Product Specific Application	Process and utilities
Range compatibility	Altivar variable speed drive ATV630 Altivar variable speed drive ATV930 PanelSeT SF and SM enclosures 23.6 in (600 mm) x 11.8 in (300 mm) PanelSeT S3D enclosure 23.6 in (600 mm) x 11.8 in (300 mm)
compatibility for Altivar Process 630-930, size:	3
Motor power kW	7.5 kW 220/240 V 11 kW 220/240 V 15 kW 380/480 V 18.5 kW 380/480 V 22 kW 380/480 V
Mounting location	1 back of enclosure mounting plate 2 inside enclosure
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic

### Complementary

Permanent permissible load	31.5 lb(US) (14.3 kg)
color	Gray RAL 7035)
Height	External: 21.9 in (555 mm) Cut-out: 19.8 in (503 mm)
Width	External: 11.6 in (295 mm) Cut-out: 9.8 in (250 mm)
Depth	Wall-enclosure separation : 0.9 in (22 mm)
Net Weight	5.406 lb(US) (2.452 kg)
Services	Configuration of enclosure pre-drilled back Factory installation drive flush mounting kit

### Environment

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

### Ordering and shipping details

Category	US1CP4E22277
----------	--------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Discount Schedule</b>	CP4E
<b>GTIN</b>	3606485433226
<b>Returnability</b>	Yes
<b>Country of origin</b>	FR

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	1.969 in (5.000 cm)
<b>Package 1 Width</b>	14.567 in (37.000 cm)
<b>Package 1 Length</b>	22.441 in (57.000 cm)
<b>Package weight(Lbs)</b>	5.406 lb(US) (2.452 kg)
<b>Unit Type of Package 2</b>	PAM
<b>Number of Units in Package 2</b>	30
<b>Package 2 Height</b>	19.685 in (50.000 cm)
<b>Package 2 Width</b>	39.370 in (100.000 cm)
<b>Package 2 Length</b>	47.244 in (120.000 cm)
<b>Package 2 Weight</b>	191.802 lb(US) (87.000 kg)

## Contractual warranty

<b>Coverage</b>	Core product
<b>Warranty</b>	18 months

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	E893f0a0-d2cc-4011-9425-3873dde70142
REACH Regulation	<a href="#">REACH Declaration</a>

### Use Again

 <b>Repack and remanufacture</b>	
Take-back	No