

# Product data sheet

Specifications



Wall mounted steel enclosure,  
PanelSeT S3D, plain door, without  
mounting plate, 1000x800x400mm,  
IP66, IK10

NSYS3D10840

**Product availability:** Non-Stock - Not normally stocked in distribution facility

## Main

Range	PanelSeT
Product name	PanelSeT S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	39.4 in (1000 mm)
Enclosure nominal width	31.5 in (800 mm)
Enclosure nominal depth	15.7 in (400 mm)
Door type	Solid
Mounting plate description	Without mounting plate
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 2 cable gland plate 1 door 1 lock

## Complementary

body type	Single piece body Gutter-shaped front rail double sheet thickness
Number of doors	Front face 1
Door opening side	Reversible 120 °)
Lock type	3 points lock, 3 mm double-bar
Accessibility for operation	Front
Removable parts	Door by hinges Cable gland plate by screws
Material	steel
Surface finish	epoxy-polyester powder
color	Gray RAL 7035)
Standards	IEC 62208 UL CUL
Product Certifications	DNV cUL UL BV GL

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Net Weight	92.6 lb(US) (42 kg)
------------	---------------------

## Environment

---

NEMA Degree of Protection	NEMA 4X/13
IK degree of protection	IK10 IEC 62262
IP degree of protection	IP66 IEC 60529

## Ordering and shipping details

---

Category	US10ES180034
Discount Schedule	0ES1
GTIN	3606480160097
Returnability	No
Country of origin	FR

## Packing Units

---

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	17.913 in (45.500 cm)
Package 1 Width	32.283 in (82.000 cm)
Package 1 Length	40.551 in (103.000 cm)
Package weight(Lbs)	91.271 lb(US) (41.400 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	4
Package 2 Height	70.079 in (178.000 cm)
Package 2 Width	39.370 in (100.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	379.195 lb(US) (172.000 kg)

## Contractual warranty

---

Coverage	Core product
Warranty	18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	390
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	E893f0a0-d2cc-4011-9425-3873dde70142
REACH Regulation	<a href="#">REACH Declaration</a>

### Use Again

#### Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No

## Offer Marketing Illustration

### Product benefits / Features

---

