

# Product data sheet

Specifications



Wall mounted steel enclosure,  
PanelSeT S3DC, plain door, without  
plain chasis, 1000x600x250mm,  
IP66, IK10

NSYS3DC10625

**Product availability: Stock - Normally stocked in distribution facility**

## Main

Range	PanelSeT
Product name	PanelSeT S3DC
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	39.4 in (1000 mm)
Enclosure nominal width	23.6 in (600 mm)
Enclosure nominal depth	9.8 in (250 mm)
Door type	Solid
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Installation accessory type	Wall-mounting
Device composition	1 body 1 door 1 lock

## Complementary

body type	Gutter-shaped front profile double sheet thickness Single piece body
Number of doors	Front face 1
Door opening side	Reversible 120 °)
Lock type	3 points lock, screw driver insert
Accessibility for operation	Front
Removable parts	Door by hinges
Material	steel
Surface finish	epoxy-polyester powder
color	Gray RAL 7035)
Standards	IEC 62208 UL CUL
Product Certifications	UL
Net Weight	56.2 lb(US) (25.5 kg)

## Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>NEMA Degree of Protection</b>	NEMA 4X/13
<b>IK degree of protection</b>	IK10 IEC 62262
<b>IP degree of protection</b>	IP66 IEC 60529

## Ordering and shipping details

<b>Category</b>	US10ES180034
<b>Discount Schedule</b>	0ES1
<b>GTIN</b>	3606480314193
<b>Returnability</b>	Yes
<b>Country of origin</b>	FR

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	12.01 in (30.500 cm)
<b>Package 1 Width</b>	24.80 in (63.000 cm)
<b>Package 1 Length</b>	43.50 in (110.500 cm)
<b>Package weight(Lbs)</b>	56.218 lb(US) (25.500 kg)
<b>Unit Type of Package 2</b>	PAM
<b>Number of Units in Package 2</b>	9
<b>Package 2 Height</b>	79.92 in (203.000 cm)
<b>Package 2 Width</b>	39.37 in (100.000 cm)
<b>Package 2 Length</b>	47.24 in (120.000 cm)
<b>Package 2 Weight</b>	537.928 lb(US) (244.000 kg)

## Contractual warranty

<b>Coverage</b>	Core product
<b>Warranty</b>	18 months

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 240

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number E893f0a0-d2cc-4011-9425-3873dde70142

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No