

Product data sheet

Specifications



Wall mounted enclosure, PanelSeT S3X, stainless steel 304L, double plain door, 1200x1000x300mm, IP55

NSYS3X121030

Product availability: Stock - Normally stocked in distribution facility

Main

Range	Spacial
Product name	Spacial S3X
enclosure type	Multi-purpose
category	Compact enclosure
nominal height	47.2 in (1200 mm)
nominal width	39.4 in (1000 mm)
nominal depth	11.8 in (300 mm)
product installation	Wall-mounting
Device composition	1 body 2 door 1 lock door 1 reinforcement frame drilled door

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail
Door type	Solid
Number of doors	Front face 2
Door opening side	Reversible 120 °)
Lock type	3 points lock, 3 mm double-bar
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Body and door stainless steel 304L Hinge stainless steel
Surface finish	Body and door Scotch-Brite® brushed
Net Weight	114.2 lb(US) (51.8 kg)

Environment

Standards	IEC 62208 UL CUL
-----------	------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Product Certifications	CAN/CSA 22 UL 508 type A
IP degree of protection	IP55 IEC 60529
IK degree of protection	IK10 IEC 62262
Environmental characteristic	Specific hygiene Corrosive

Ordering and shipping details

Category	US10ES180034
Discount Schedule	0ES1
GTIN	3606480154997
Returnability	Yes
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	12.598 in (32.000 cm)
Package 1 Width	39.764 in (101.000 cm)
Package 1 Length	48.031 in (122.000 cm)
Package weight(Lbs)	114.200 lb(US) (51.800 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	3
Package 2 Height	46.063 in (117.000 cm)
Package 2 Width	39.370 in (100.000 cm)
Package 2 Length	48.031 in (122.000 cm)
Package 2 Weight	395.510 lb(US) (179.400 kg)

Contractual warranty

Coverage	Core product
Warranty	18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 770

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number E893f0a0-d2cc-4011-9425-3873dde70142

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No

Offer Marketing Illustration

Product benefits / Features

High resistance to corrosion

Earthing studs included

Large choice of dimensions & accessories

Built to last

Easy to equip
Easy to maintain

Easy & quick assembly