


Product data sheet

Specifications



Cable ducting support to be used with 22mm-diameter products

NSYSPCP

Main

Accessory / separate part category	Cable management accessory
Product or component type	Support
Product destination	Cable duct
Range compatibility	PanelSeT PLA PanelSeT PLS PanelSeT PLM PanelSeT SBM PanelSeT S3D PanelSeT S3CM PanelSeT CRN
Anwendung	Multi-purpose
Mounting support	Door
Device composition	1 support
Quantity per set	Set of 10

Complementary

Material	Galvanised steel
Fixing mode	By screws on 22 mm equipment
Height	100 mm
Width	30 mm
Depth	11.5 mm
Diameter	22.5 mm 0 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	0.700 cm
Package 1 Length	10.500 cm
Package 1 Weight	30.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	2.000 cm
Package 2 Width	7.000 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Length	10.500 cm
Package 2 Weight	301.000 g
Unit Type of Package 3	CAR
Number of Units in Package 3	320
Package 3 Height	20.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	9.632 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration

Use Again

 Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No