

Product data sheet

Specifications



ABS industrial box, PanelSeT TBS,
291x168x341mm, int.
275x160x325mm, high plain cover,
IP66, IK07, RAL 7035

NSYTBS342916H

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	PanelSeT
Product name	Thalassa TBS
Device Application	Multi-purpose
Category	Industrial box
Height	13.4 in (341 mm)
Width	11.5 in (291 mm)
Depth	6.6 in (168 mm)
Internal height	12.8 in (325 mm)
Internal width	10.8 in (275 mm)
Internal depth	6.3 in (160 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 cover 4 cover screw
Body type	One piece moulded
Type of front cover	High plain cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	ABS with 45% of post-industrial recycled content
color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	TÜV
Electrical Insulation Class	Class II
IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK07 conforming to IEC 62262
Glow wire resistance	1202 °F (650 °C) IEC 60695-2-11
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
Operating temperature	-13...140 °F (-25...60 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net Weight	3.66 lb(US) (1.66 kg)
------------	-----------------------

Ordering and shipping details

Category	US10ES180033
Discount Schedule	0ES1
GTIN	3606480165412
Returnability	No
Country of origin	HU

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	7.28 in (18.500 cm)
Package 1 Width	11.81 in (30.000 cm)
Package 1 Length	14.17 in (36.000 cm)
Package weight(Lbs)	3.594 lb(US) (1.630 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	3
Package 2 Height	15.75 in (40.000 cm)
Package 2 Width	15.75 in (40.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	10.781 lb(US) (4.890 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	36
Package 3 Height	53.15 in (135.000 cm)
Package 3 Width	31.50 in (80.000 cm)
Package 3 Length	47.24 in (120.000 cm)
Package 3 Weight	156.528 lb(US) (71.000 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	16
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Minimum percentage of recycled plastic content	45
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration

Dimensions




Image of product / Alternate images

Alternative

