


Product data sheet

Specifications



Terminal block, Linergy TR, push-in type, feed through, 3 points, 2.5mm², grey, set of 50

NSYTRP23

Product availability: Stock - Normally stocked in distribution facility

Main

Range	Linergy
Product name	Linergy TR
Product or Component Type	Terminal block
Device short name	TRP
Accessory / separate part category	Connection accessory
Terminal block type	Passthrough
Terminal block level	1
Mounting Mode	Clip-on
Nominal cross section	0.004 in ² (2.5 mm ²)
Length	2.4 in (60.5 mm)
color	Gray
Quantity per Set	Set of 50

Complementary

Width	0.2 in (5.2 mm)
Height	1.4 in (36.5 mm)
Connections - terminals	1 x push-in upstream 2 x push-in downstream
number of connections	3
Connection position	Top
Number of measurement input	2
Cable cross section	0.0002...0.004 in ² (0.14...2.5 mm ²), flexible without cable end 0.0002...0.006 in ² (0.14...4 mm ²), solid with cable end 0.0003...0.004 in ² (0.2...2.5 mm ²), solid without cable end 0.001...0.004 in ² (0.8...2.5 mm ²), flexible with cable end
Wire stripping length	0.4 in (10 mm)
Tool type	Connection without tool Disconnection flat screwdriver
[Ue] rated operational voltage	800 V EN/IEC 60947-7-1 600 V CSA 600 V UL
Line Rated Current	24 A EN/IEC 60947-7-1 20 A CSA 20 A UL

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Material	Polyamide 6/6: insulating case Copper alloy: connector and screw Copper alloy: commoning link Chromium-nickel steel: spring
Dielectric loss	0.01 at 1 MHz IEC 60250 0.01 at 1 MHz VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 M Ω .m IEC 60093 10000 M Ω .m VDE 0303-T30
Surface resistance	1000 G Ω IEC 60093 1000 G Ω VDE 0303-T30
Creep resistance	500 CTI (> 400 kV) IEC 60093 500 CTI (> 400 kV) VDE 0303-T30
Flame retardance	V0 0.03 in (0.8 mm) UL 94
Net Weight	0.3 oz (8.8 g)
Range compatibility	PrismaSeT G PrismaSeT P PrismaSet HD PrismaSeT Pack 250 PanelSeT Mureva PrismaSeT XS TeSys
Product Compatibility	Spacial enclosures

Environment

Product Certifications	UL GL VDE CSA
Dielectric strength	1000 V IEC 60243-1
Ambient air temperature for operation	-40...266 °F (-40...130 °C) IEC 60216-1 -40...266 °F (-40...130 °C) VDE 0304-T21

Ordering and shipping details

Category	US10CP521715
Discount Schedule	0CP5
GTIN	3606480533167
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.378 in (3.500 cm)
Package 1 Width	0.197 in (0.500 cm)
Package 1 Length	2.362 in (6.000 cm)
Package weight(Lbs)	0.282 oz (8.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	50

Package 2 Height	1.772 in (4.500 cm)
Package 2 Width	2.756 in (7.000 cm)
Package 2 Length	10.630 in (27.000 cm)
Package 2 Weight	15.379 oz (436.000 g)
Unit Type of Package 3	S03
Number of Units in Package 3	1250
Package 3 Height	11.811 in (30.000 cm)
Package 3 Width	11.811 in (30.000 cm)
Package 3 Length	15.748 in (40.000 cm)
Package 3 Weight	25.084 lb(US) (11.378 kg)

Contractual warranty

Warranty	18 months
-----------------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 5

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

Halogen content performance Halogen free plastic parts product

PVC free Yes

Silicon free Yes

Use Again

Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No