

Product data sheet

Specifications



Terminal block, Linergy TR, spring type, protective earth, 2 points, 2.5mm², green-yellow, set of 50

NSYTRR22PE

Main

Range	Linergy
Product name	Linergy TR
Product or component type	Terminal block
Device short name	TRR
Terminal block type	Protective earth
Terminal block level	1
Mounting mode	Clip-on
Nominal cross section	2.5 mm ²
Length	48.5 mm
Colour	Green-yellow
Quantity per set	Set of 50

Complementary

Width	5.2 mm
Height	36.5 mm
Connections - terminals	1 x spring terminal: upstream 1 x spring terminal: downstream
number of connections	2
Connection position	Top
Number of measurement input	2
Cable cross section	0.08...4 mm ² , solid 0.2...2.5 mm ² , flexible with cable end 0.08...2.5 mm ² , flexible without cable end
Wire stripping length	10 mm
Tool type	Connection: flat screwdriver Disconnection: flat screwdriver
Material	Polyamide 6/6: insulating case
Dielectric loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 MΩ.m conforming to IEC 60093 10000 MΩ.m conforming to VDE 0303-T30
Surface resistance	1000 GΩ conforming to IEC 60093 1000 GΩ conforming to VDE 0303-T30

Creep resistance	500 CTI (> 400 kB) conforming to IEC 60093 500 CTI (> 400 kB) conforming to VDE 0303-T30
Flame retardance	V0, thickness 0.8 mm conforming to UL 94
Net weight	10 g
Range compatibility	PrismaSeT P PrismaSeT G PrismaSet HD PrismaSeT Pack 250 PanelSeT Mureva PrismaSeT XS TeSys
Product compatibility	Spacial enclosures

Environment

Product certifications	CSA GL UL DNV VDE
Dielectric strength	1000 V conforming to IEC 60243-1
Ambient air temperature for operation	-40...130 °C conforming to IEC 60216-1 -40...130 °C conforming to VDE 0304-T21

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	7.000 cm
Package 1 Length	6.750 cm
Package 1 Weight	9.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	50
Package 2 Height	4.500 cm
Package 2 Width	7.000 cm
Package 2 Length	27.000 cm
Package 2 Weight	495.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	1100
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	11.385 kg

Contractual warranty

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	5
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Again

Repack and remanufacture

End of life manual availability	No need of specific recycling operations
Take-back	No