

Product availability : Stock - Normally stocked in distribution facility



### Main

Product or component type	Circuit breaker
Range of product	PowerPact R
Trip unit technology	Electronic standard Micrologic 5.0 LSI

### Complementary

[Ie] rated operational current	1000 A
System Voltage	600 V AC
Mounting mode	Unit mount
Poles description	3P
Breaking capacity	65 kA at: 240 V AC 35 kA at: 480 V AC 18 kA at: 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Breaking capacity code	G
Electrical connection	Busbar connection load Busbar connection line
Height	16.24 in
Width	16.53 in
Depth	14.49 in

### Environment

Product certifications	CSA IEC UL listed
------------------------	-------------------------

### Ordering and shipping details

Category	01245 - RG,H,J,K,L,N UNIT MT BREAKERS
----------	---------------------------------------

Discount Schedule	DE2
GTIN	00785901554905
Nbr. of units in pkg.	1
Package weight(Lbs)	52
Returnability	Y
Country of origin	US

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014

### Contractual warranty

Warranty period	18 months
-----------------	-----------