

Product data sheet

Specifications



Circuit breaker accessory,
communication kit, BSCM V2,
3.00m NSX cable, greater than
480V

S434303BX

Coming soon

Launching in: 1 May 2025

Product availability: Non-Stock - Not normally stocked in
distribution facility

Main

Product or Component Type	Communication kit
Device short name	breaker status control module

Complementary

[Ue] rated operational voltage	> 480 V <= 690 V
Accessory / Separate Part Type	NSX cable
Cable length	9.84 ft (3.00 m)

Environment

Standards	UL 489 UL 60947-4-1 IEC 60947-2 CSA C22.2 No 5-16 CSA C22.2 No 14 FCC
-----------	--

Ordering and shipping details

Category	US10DE201103
Discount Schedule	0DE2
GTIN	3606487084914
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.45 in (11.3 cm)
Package 1 Width	4.96 in (12.6 cm)
Package 1 Length	6.54 in (16.6 cm)
Package 1 Weight	9.6 oz (272 g)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	420bf2d3-b34e-4e58-baf2-c96c36dac5a4
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free plastic parts product

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.