


Product data sheet

Specifications



servo motor SH3 040
0,21Nm,key,multi,brake,90°conn,
IP54/IP65,9k RPM

SH30401P17F2000

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Compatibility	PacDrive 3
Device short name	SH3
Product or Component Type	Servo motor

Complementary

Maximum mechanical speed	9000 rpm
[Us] rated supply voltage	115...480 V
Phase	Three phase
Continuous stall current	1.12 A
Continuous stall torque	1.86 lbf.in (0.21 N.m) 115...480 V three phase
Continuous power	170 W
Peak stall torque	6.64 lbf.in (0.75 N.m) 480 V three phase
Nominal output power	77 W 115 V single phase 77 W 230 V single phase 166 W 400 V three phase 166 W 480 V three phase
Nominal torque	1.558 lbf.in (0.176 N.m) 115 V single phase 1.558 lbf.in (0.176 N.m) 230 V single phase 1.629 lbf.in (0.184 N.m) 400 V three phase 1.629 lbf.in (0.184 N.m) 480 V three phase
Nominal speed	4000 rpm 115 V single phase 4000 rpm 230 V single phase 9000 rpm 400 V three phase 9000 rpm 480 V three phase
Maximum current Irms	4.5 A
Shaft end	Parallel key
Shaft diameter	0.3 in (8 mm)
Shaft length	1.0 in (25 mm)
Key width	0.1 in (3 mm)
IP degree of protection	IP54 shaft bushing without shaft seal ring: conforming to IEC 60034-5 IP65 motor: conforming to IEC 60034-5 IP65 shaft bushing: conforming to IEC 60034-5
Encoder type	Absolute multiturn SinCos Hiperface
Speed feedback resolution	16 periods
Holding brake	With
Holding torque	3.5 lbf.in (0.4 N.m)
Mounting Support	International standard flange

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Motor flange size	1.6 in (40 mm)
Electrical Connection	Rotatable right angled connector
Torque constant	0.19 N.m/A 248 °F (120 °C)
Back emf constant	13.6 V/krpm 68 °F (20 °C)
Number of motor poles	5.0
Rotor inertia	0.04 kg.cm²
Stator resistance	17.2 Ohm
Stator inductance	7.3 mH
Type of cooling	Natural convection
Length	3.9 in (99.4 mm)
Centring collar diameter	1.2 in (30 mm)
Centring collar depth	0.10 in (2.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.2 in (4.5 mm)
Circle diameter of the mounting holes	1.8 in (46 mm)
Net Weight	1.3 lb(US) (0.6 kg)
Sizing reference	SH30402P
Network number of phases	3
Temperature copper hot	248 °F (120 °C)
compatible drive output current 3s peak 2	6 A
Electrical connection	rotatable right angled connector

Ordering and shipping details

Category	US1PC5218359
Discount Schedule	PC52
GTIN	3606485467535
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.3 in (11.0 cm)
Package 1 Width	6.7 in (17.0 cm)
Package 1 Length	9.4 in (24.0 cm)
Package weight(Lbs)	22.1 oz (627.0 g)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	408
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	Ead0850d-370a-47c5-8cf7-1d93c2c974a4
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No