## SM952A127080

Hyde Park, Ultrasonic sensor, dual level, dual setpoint, 30 mm barrel, 12 24 V DC



## Main

Sensor Type Ultrasonic sensor  Series name Superprox 900  Device short name SM952  Sensor design Cylindrical M30  Type of sensing window Adjustable  Material Plastic  Enclosure Material ULTEM	Range of Product	Hyde Park
Device short name SM952 Sensor design Cylindrical M30 Type of sensing window Adjustable Material Plastic	Sensor Type	Ultrasonic sensor
Sensor design Cylindrical M30  Type of sensing window Adjustable  Material Plastic	Series name	Superprox 900
Type of sensing window Adjustable  Material Plastic	Device short name	SM952
Material Plastic	Sensor design	Cylindrical M30
	Type of sensing window	Adjustable
Enclosure Material ULTEM	Material	Plastic
	Enclosure Material	ULTEM
Front material Silicone rubber	Front material	Silicone rubber
Type of output signal Discrete	Type of output signal	Discrete
Discrete output function 1 NC	Discrete output function	1 NC
ISO thread M30 x 1.5	ISO thread	M30 x 1.5
Wiring Technique 4-wire	Wiring Technique	4-wire
[Us] rated supply 1224 V DC overload and short-circuit protection voltage		1224 V DC overload and short-circuit protection
Supply voltage limits 1028 V DC	Supply voltage limits	1028 V DC
Discrete output type PNP	Discrete output type	PNP
Electrical connection Male connector M12 4 pins	Electrical connection	Male connector M12 4 pins
Product Specific Dual-level - setpoint Application	•	Dual-level - setpoint

## Complementary

Complementary	
[Sn] nominal sensing distance	3.28 ft (1 m)
[Sd] sensing range	0.173.28 ft (0.05081 m)
Maximum differential travel	0.10 in (2.5 mm)
Blind zone	2.01 in (51 mm)
Transmission frequency	200 kHz
Repeat accuracy	0.87 %
Beam angle	10 °
Minimum size of detected object	Cylinder diameter 1.6 mm - up to 305 mm sensing distance
Current Consumption	100 mA
Maximum switching current	100 mA reverse polarity protection
Height	1.18 in (30 mm)
Width	1.37 in (34.7 mm)
Depth	1.18 in (30 mm)
Length	3.78 in (96 mm)
Net Weight	0.57 lb(US) (0.26 kg)

## Environment

Product Certifications	UL
Marking	CE
NEMA degree of protection	NEMA 4X indoor use only)
IP degree of protection	IP67
Ambient Air Temperature for Operation	32122 °F (050 °C)
Ambient Air Temperature for Storage	-4176 °F (-2080 °C)
Relative humidity	100 % without condensation
Vibration resistance	+/-1 mm 1055 Hz)IEC 60068-2-6

Shock resistance	30 gn in all 3 axes 11 ms IEC 60068-2-27
Resistance to electromagnetic fields	9.14 V/m (10 V/m) level 3 IEC 61000-4-3
Resistance to fast transients	1 kV level 3 IEC 61000-4-4
Ordering and shipping details	
Category	22490-SENSORS-ULTRASONIC (XX5,6)
Discount Schedule	DS2
GTIN	3389119119306
Returnability	No
Country of origin	US
Packing Units Unit Type of Package 1 Number of Units in Package 1	PCE 1
<del>-</del>	
Package 1 Height	1.80 in (4.572 cm)
Package 1 Width	3.90 in (9.906 cm)
Package 1 Length	5.30 in (13.462 cm)
Package 1 Weight	12.80 oz (362.874 g)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

18 months

Contractual warranty

Warranty