

# Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 1000VA, Tower, 120V, 8x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT1000C

## Overview

**Presentation** Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

**Lead time** Usually in Stock

## Main

**Product or component type** Uninterruptible power supply (UPS)

## Complementary

**Communication port type** SmartConnect Ethernet port  
SmartSlot

**Software package** SmartConnect software for remote power monitoring feature availability varies by terms of use

## Batteries & Runtime

**Run Time** [View Runtime Graph](#)

**Efficiency** [View Efficiency Graph](#)

**Battery type** Lead-acid battery

**Extended runtime** 0

**Number of battery filled slots** 0

**Number of battery free slots** 0

**Battery recharge time** 3 h

**Number of battery replacement quantity** 1

**Battery life** 3...5 year(s)

**Replacement battery** [RBC6](#)

**Battery charger power** 88 W rated

## General

**Provided equipment** User manual  
USB cable

**Number of power module** 0

**Number of power module filled slots** 0

**Number of power module free slots** 0

**product web sub-family** Cloud-enabled monitoring

Redundant	No
-----------	----

## Physical

Cable length	1.8 m
Number of cables	1
Colour	Black
Height	21.9 cm
Width	17.1 cm
Depth	43.9 cm
Net weight	20.1 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

## Input

Main Input Voltage	120 V
Other Input Voltage	110 V 125 V
Input Connection Type	NEMA 5-15P
Input voltage limits	75...154 V adjustable 82...144 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Main Output Voltage	120 V
Other Output Voltage	110 V 125 V
Rated power in W	700 W
Rated power in VA	1000 VA
output connection type	8 NEMA 5-15R
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	700 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product certifications	cULus ENERGY STAR V2.0 (USA)
------------------------	---------------------------------

---

Equipment protection policy	Lifetime : \$150000
-----------------------------	---------------------

## Environmental

---

Acoustic level	41 dBA
Heat dissipation	175 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

---

Control panel	Multifunction LCD status and control console
Free slots	1
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use

---

Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

---

Surge energy rate	680 J
-------------------	-------

---

Noise suppression Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33 cm
Package 1 Width	59 cm
Package 1 Length	33 cm
Package 1 Weight	22.64 kg

## Contractual warranty

---

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	-----------------------------------------------------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 995

Environmental Disclosure [Product Environmental Profile](#)

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number B2b22a56-41f2-497e-9ea6-cf093b3b8bd3

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

#### Energy efficiency

Energy Efficiency Optimized Energy efficient product

 ENERGY STAR® ENERGY STAR UPS V2.0 (USA)

### Use Again

#### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back Yes

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Dimensions

---



©2019 APC

Image of product / Alternate images

Alternative

---

