# Product data sheet
## Characteristics

# TSXCDP302
## rolled ribbon connecting cable - for I/O module with HE10 connectors - 3 m



### Main

| | |
|---|---|
| Range of Product | Modicon Premium Automation platform |
| Accessory / separate part designation | Rolled ribbon connecting cable |
| Accessory / separate part type | Connecting cable |
| Accessory / separate part categor | Connection accessories |
| Accessory / separate part destination | Telefast 2 sub-base<br>I/O module fitted with HE10 connectors |
| Product Specific Application | Encoder supply 5 V/10...30 V DC<br>Auxiliary inputs supply 24 V DC |

### Complementary

| | |
|---|---|
| Product Compatibility | ABE7H08R10<br>TSXCTY2C<br>ABE7H16R20 |
| Cable length | 9.8 ft (3 m) |
| Electrical connection | 2 connectors HE10, 20 ways |
| Wire section | 0.0001 in² (0.08 mm²) |
| AWG Gauge | AWG 28 |
| Current per channel | 0.1 A |
| Net Weight | 0.55 lb(US) (0.25 kg) |

### Ordering and shipping details

| | |
|---|---|
| Category | US1PC1422556 |
| Discount Schedule | PC14 |
| GTIN | 3389110603095 |
| Returnability | No |
| Country of origin | US |

### Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 0.6 in (1.5 cm) |
| Package 1 Width | 6.3 in (16.0 cm) |
| Package 1 Length | 7.09 in (18.0 cm) |
| Package 1 Weight | 6.2 oz (175.0 g) |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 20 |
| Package 2 Height | 11.8 in (30.0 cm) |
| Package 2 Width | 11.8 in (30.0 cm) |
| Package 2 Length | 15.7 in (40.0 cm) |
| Package 2 Weight | 7.7 lb(US) (3.5 kg) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

| | |
|---|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |