

# Product data sheet

Specifications



## Enclosed switch disconnecter, TeSys Control, for ON/emergency stop, 10A, IP65

VCF02GE

### Main

|                           |   |
|---------------------------|---|
| Range                     | TeSys                                       |
| Product name              | TeSys VARIO                                 |
| Device short name         | VCF   |
| Product or component type | Enclosed emergency stop switch disconnecter |
| Performance level         | High performance                            |
| Poles description         | 3P  |
| Control type              | Rotary handle                               |
| Handle colour             | Red   |
| Handle front plate colour | Yellow                                      |
| Rotary handle padlocking  | 1 to 3 padlocks 4...8 mm                    |

### Complementary

|  |  |
|--|--|
| Marking                                      | 0 - 1  |
| [Ue] rated operational voltage               | 690 V AC   |
| [Uimp] rated impulse withstand voltage       | 8 kV   |
| [Ithe] conventional enclosed thermal current | 10 A   |
| [Ie] rated operational current               | 8.1 A (AC-23A) at 400 V  |
| Rated operational power in W                 | 4 kW at 400 V (AC-23)<br>3 kW at 400 V (AC-3)  |
| Intermittent duty class                      | 30   |
| Making capacity ( I rms)                     | 120 A at 400 V AC-21A<br>120 A at 400 V AC-22A<br>120 A at 400 V AC-23A              |
| [Icm] rated short-circuit making capacity    | 1 kA at 400 V at Ipeak   |
| [Icw] rated short-time withstand Rms current | 300 A at 400 V duration: 1 s   |
| Rated conditional short-circuit current      | 10 kA at 400 V - associated fuse 12 A aM<br>10 kA at 400 V - associated fuse 12 A gG |
| Breaking capacity                            | 120 A at 400 V (AC-21A)<br>120 A at 400 V (AC-22A)<br>120 A at 400 V (AC-23A)        |
| Mechanical durability                        | 100000 cycles  |
| Electrical durability                        | 100000 cycles AC-21<br>30000 cycles DC-1...5   |
| Environmental characteristic                 | Standard environment   |

|                              |   |
|------------------------------|---|
| Suitability for isolation    | Yes   |
| Connections - terminals      | Screw clamp terminals 10 mm <sup>2</sup> - solid<br>Screw clamp terminals 6 mm <sup>2</sup> - flexible - with cable end |
| Tightening torque            | 2.1 N.m - on screw clamp terminals  |
| Fire resistance              | 960 °C conforming to IEC 60595-2-1  |
| handle front plate dimension | 60 x 60 mm  |
| Height                       | 146 mm  |
| Width                        | 90 mm   |
| Depth                        | 131 mm  |
| Net weight                   | 0.5 kg  |

## Environment

|                                       |  |
|---------------------------------------|--|
| Standards                             | IEC 60947-4-1<br>IEC 60204   |
| Protective treatment                  | TC   |
| IP degree of protection               | IP65 conforming to IEC 60529   |
| Mechanical robustness                 | Vibrations 10...150 Hz (1 gn) conforming to IEC 60068-2-6<br>Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27 |
| Ambient air temperature for operation | -20...50 °C  |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 14.500 cm |
| Package 1 Width              | 11.000 cm |
| Package 1 Length             | 16.000 cm |
| Package 1 Weight             | 479.000 g |
| Unit Type of Package 2       | S03       |
| Number of Units in Package 2 | 7         |
| Package 2 Height             | 30 cm     |
| Package 2 Width              | 30 cm     |
| Package 2 Length             | 40 cm     |
| Package 2 Weight             | 3.800 kg  |
| Unit Type of Package 3       | P06       |
| Number of Units in Package 3 | 56        |
| Package 3 Height             | 75.000 cm |
| Package 3 Width              | 60.000 cm |
| Package 3 Length             | 80.000 cm |
| Package 3 Weight             | 38.928 kg |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

|                                  |   |
|----------------------------------|---|
| Total lifecycle Carbon footprint | 17  |
| Environmental Disclosure         | <a href="#">Product Environmental Profile</a> |

## Use Better

### Materials and Substances

|  |  |
|--|--|
| Packaging made with recycled cardboard | Yes  |
| Packaging without single use plastic   | Yes  |
| <a href="#">EU RoHS Directive</a>      | Compliant with Exemptions  |
| SCIP Number                            | 9ea58720-3cf9-4883-9af8-9d64d3981af2   |
| REACH Regulation                       | <a href="#">REACH Declaration</a>  |
| California proposition 65              | <b>WARNING:</b> This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

## Use Again

### Repack and remanufacture

|                                 |   |
|---------------------------------|---|
| End of life manual availability | No need of specific recycling operations  |
| Take-back                       | No  |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |