



Main

Product or Component Type	Additional output module
Range Compatibility	Altivar Machine ATV340 Easy Altivar 610 Altivar&Nbsp;Process ATV900 Altivar Process ATV600
Input/Output Type	3 relay output
Discrete output number	3
Discrete output type	R4, R5, R6) relay normally open 1 ms

Complementary

Electrical durability	100000 cycles
Minimum switching current	5 mA 24 V DC
Maximum switching current	2 A 250 V AC inductive, cos phi = 0.4 5 ms 2 A 30 V DC inductive, cos phi = 0.4 5 ms 5 A 250 V AC resistive, cos phi = 1 5 ms 5 A 30 V DC resistive, cos phi = 1 5 ms
Electrical connection	Screw terminal block, 1.5 mm ² / AWG 16, 4.4 lbf.in (0.5 N.m)
Net Weight	0.9 lb(US) (0.4 kg)

Ordering and shipping details

Category	US1CP4E22207
Discount Schedule	CP4E
GTIN	3606480702532
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.6 in (6.5 cm)
Package 1 Width	5.1 in (13.0 cm)
Package 1 Length	7.5 in (19.0 cm)
Package 1 Weight	5.4 oz (152.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	6.865 lb(US) (3.114 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations