

Product data sheet

Specifications



dPAC module, Altivar, 10/100Mbps, 2 x RJ45 connectors

VW3A3530D

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	EcoStruxure Automation Expert
Range Compatibility	Altivar Machine ATV340 Altivar Process ATV600 Altivar Process ATV900
Product or Component Type	Processor module
[Us] rated supply voltage	24 V DC supplied by the host Altivar drive

Complementary

Input/output number	23 discrete input/output 7 analog input/output 1 master encoder input
Data backed up	32 MB flash memory backup of user programs
Realtime clock	With VW3A1111 Altivar graphic display terminal
Battery type	CR2032 lithium non-rechargeable 10 year(s)
Integrated connection type	Dual-port Ethernet 2 RJ45 connectors
Port Ethernet	Ethernet 10BASE-T/100BASE-TX - 2 copper cable
Exchange mode	Half duplex and full duplex
Communication Network Type	IPv4 (internet protocol) IPv6 (internet protocol)
Communication service	Modbus TCP/IP server Modbus TCP/IP client SysLog server DPWS (IPv6) EcoStruxure automation expert archive EcoStruxure automation expert cross-communication EcoStruxure automation expert HMI Altivar drive Modbus TCP/IP server NTP synchronization OPC UA client OPC UA server SNTP client NetIO server WebSocket server
Topology	Daisy chain Star
Web server	Altivar drive Embedded HTTPS server
Web services	Save/restore drive configuration Drive setting and diagnostic Energy monitoring Widgets (ID, control, data table, diagnostic, charts) Customizable home page Drive monitor Customizable dashboards

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Local signalling	1 LED for RUN/ERR (Module Status)
	1 LED for NS (Network Status)
	1 LED for TX/RX (Transmit/Receive port 1)
Product Weight	0.33 lb(US) (0.15 kg)

Environment

Product Certifications	CE UKCA
------------------------	------------

Ordering and shipping details

Category	US1PC1522555
Discount Schedule	PC15
GTIN	03606481007223
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.56 in (6.500 cm)
Package 1 Width	5.12 in (13.000 cm)
Package 1 Length	7.48 in (19.000 cm)
Package 1 Weight	5.573 oz (158.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	6.647 lb(US) (3.015 kg)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

 Repack and remanufacture	
Take-back	No