



### Main

Range of Product	Altivar
Product or Component Type	Encoder interface module
Range Compatibility	Altivar 32 Altivar Machine ATV320
[Us] rated supply voltage	5 V 5...5.5 V)
Number of pulses per revolution	3600 ATV32

### Complementary

Product compatibility	ATV32 >= V1.8)
Protection Type	Overload protection Short-circuit protection
Maximum operating frequency	250 kHz
Input signal	TTL
Electrical connection	Terminal 1.5 mm <sup>2</sup> AWG 16), encoder, 200 mA
Net Weight	0.7 lb(US) (0.3 kg)

### Ordering and shipping details

Category	US1PC5118297
Discount Schedule	PC51
GTIN	3606480517259
Returnability	No
Country of origin	ID

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.850 in (4.700 cm)
Package 1 Width	2.559 in (6.500 cm)
Package 1 Length	3.543 in (9.000 cm)
Package 1 Weight	1.940 oz (55.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	96
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	13.384 lb(US) (6.071 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations