


Product data sheet

Specifications



braking resistor - 27 ohm - 400 W -
cable 2 m - IP65

VW3A7604R20

**Product availability: Non-Stock - Not normally stocked in
distribution facility**

Main

Range of Product	Lexium Altivar
Range Compatibility	Lexium 15 Lexium 52 Lexium 32i Lexium 32 Lexium 05 Lexium 28 Easy Lexium 16
Product compatibility	Motion servo drive LXM16D 0.75 kW, 200...230 V, single phase Motion servo drive LXM16D 1 kW, 200...230 V, single phase Motion servo drive LXM16D 1.5 kW, 200...230 V, single phase
Product or Component Type	Braking resistor
Ohmic value	27 Ohm

Complementary

Energy peak	10500 J 480 V 11400 J 400 V 18100 J 230 V 25500 J 115 V
Continuous power	400 W
Protection Type	Thermal protection via the servo drive
Product Weight	3.24 lb(US) (1.47 kg)
Cable length	6.6 ft (2 m)

Environment

IP Degree of Protection	IP65
Ambient Air Temperature for Storage	-13...185 °F (-25...85 °C)
Ambient air temperature for operation	32...122 °F (0...50 °C)

Ordering and shipping details

Category	US1PC5118263
Discount Schedule	PC51
GTIN	3389119207188
Returnability	No
Country of origin	CZ

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.772 in (4.500 cm)
Package 1 Width	4.921 in (12.500 cm)
Package 1 Length	15.551 in (39.500 cm)
Package weight(Lbs)	3.558 lb(US) (1.614 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	10.236 in (26.000 cm)
Package 2 Width	8.661 in (22.000 cm)
Package 2 Length	16.535 in (42.000 cm)
Package 2 Weight	21.976 lb(US) (9.968 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	108
Package 3 Height	37.402 in (95.000 cm)
Package 3 Width	31.496 in (80.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	439.646 lb(US) (199.420 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No


Use Again

Repack and remanufacture	
Take-back	No

Dimensions Drawings

Braking Resistor

Dimensions



Dimensions in mm

b	b1	c	c1	H
257	216	30	–	204

Dimensions in in.

b	b1	c	c1	H
10.11	8.50	1.18	–	8.03