

# VW3A9704

metal conduit box UL, Altivar, Nema type1, IP21, for variable speed drive, size 6



## Main

Range of Product	Altivar
Accessory / separate part categor	Protection accessory
Accessory / separate part type	IP21 protection kit
Product compatibility	<p>Variable speed drive ATV630 55 kW, normal duty 200...240 V</p> <p>Variable speed drive ATV630 75 kW, normal duty 200...240 V</p> <p>Variable speed drive ATV630 110 kW, normal duty 380...480 V</p> <p>Variable speed drive ATV630 132 kW, normal duty 380...480 V</p> <p>Variable speed drive ATV630 160 kW, normal duty 380...480 V</p> <p>Variable speed drive ATV630 90 kW, heavy duty 380...480 V</p> <p>Variable speed drive ATV630 110 kW, heavy duty 380...480 V</p> <p>Variable speed drive ATV630 132 kW, heavy duty 380...480 V</p> <p>Variable speed drive ATV610 110 kW 380...480 V</p> <p>Variable speed drive ATV610 132 kW 380...480 V</p> <p>Variable speed drive ATV610 160 kW 380...480 V</p> <p>Variable speed drive ATV930 55 kW, normal duty 200...240 V</p> <p>Variable speed drive ATV930 75 kW, normal duty 200...240 V</p> <p>Variable speed drive ATV930 110 kW, normal duty 380...480 V</p> <p>Variable speed drive ATV930 132 kW, normal duty 380...480 V</p> <p>Variable speed drive ATV930 160 kW, normal duty 380...480 V</p> <p>Variable speed drive ATV930 45 kW, heavy duty 200...240 V</p> <p>Variable speed drive ATV930 55 kW, heavy duty 200...240 V</p> <p>Variable speed drive ATV930 90 kW, heavy duty 380...480 V</p> <p>Variable speed drive ATV930 110 kW, heavy duty 380...480 V</p> <p>Variable speed drive ATV930 132 kW, heavy duty 380...480 V</p>
Accessory / separate part destination	Variable speed drive
Range Compatibility	<p>Easy Altivar 610</p> <p>Altivar&amp;Nbsp;Process ATV600</p> <p>Altivar&amp;nbsp;Process ATV900</p>

## Complementary

Kit composition	<p>Instruction sheet</p> <p>Fixing accessories</p> <p>All the mechanical parts including a pre-cut plate for fixing the cable glands</p>
Net Weight	19.8 lb(US) (9 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

Category	US1CP4E22205
Discount Schedule	CP4E
GTIN	3606485410876
Returnability	Yes
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.402 in (31.500 cm)
Package 1 Width	14.606 in (37.100 cm)
Package 1 Length	15.945 in (40.500 cm)
Package 1 Weight	23.067 lb(US) (10.463 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	18
Package 2 Height	43.307 in (110.000 cm)
Package 2 Width	31.496 in (80.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	444.232 lb(US) (201.500 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
PVC free	Yes