

Product data sheet

Specifications



pre-assembled cable kit for safe torque off signal - 3 M

VW3L20010R30

Main

Product or component type	Pre-assembled cable kit for safe torque off signal - 3 M
Accessory / separate part type	Cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	For drives with printed circuit board connectors for safe torque off
Cable length	3 m
Additional information	With integrated cable entry with strain relief

Complementary

Range compatibility	Lexium ILS Lexium ILE Lexium ILA
Electrical connection	1 connector M8 for safe torque off Cable end open for drive Printed circuit board connector
Net weight	0.5 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	30.0 cm
Package 1 Length	30.0 cm
Package 1 Weight	500.0 g

Contractual warranty

Warranty	18 months
----------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

 Repack and remanufacture	
Take-back	No