

Product data sheet

Specifications



power cable - between servomotor
BDH, BSH and servodrive -
4x1.5mm²+2x1mm² - 10m

VW3M5101R100

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Power cable
Accessory / Separate Part Type	Preassembled power cordset
Accessory / separate part category	Connection accessories
Product compatibility	Servo motor BMH, 1 2.8 in (70 mm)) Servo motor BMH, 2 2.8 in (70 mm)) Servo motor BMH, 3 2.8 in (70 mm)) Servo motor BMH, 1 3.9 in (100 mm)) Servo motor BMH, 2 3.9 in (100 mm)) Servo motor BMH, 3 3.9 in (100 mm)) Servo motor BMH, 1 5.5 in (140 mm)) Servo motor BSH, 1 2.2 in (55 mm)) Servo motor BSH, 2 2.2 in (55 mm)) Servo motor BSH, 3 2.2 in (55 mm)) Servo motor BSH, 1 2.8 in (70 mm)) Servo motor BSH, 2 2.8 in (70 mm)) Servo motor BSH, 3 2.8 in (70 mm)) Servo motor BSH, 1 3.9 in (100 mm)) Servo motor BSH, 2 3.9 in (100 mm)) Servo motor BSH, 3 3.9 in (100 mm)) Servo motor BSH, 1 5.5 in (140 mm))
Accessory / separate part destination	Between servo motor and servo drive
Range Compatibility	Lexium 32 Lexium 05 Lexium 15
Cable length	32.8 ft (10 m)
Cable composition	4 x 1.5 mm ² + 2 x 1 mm ²

Complementary

Electrical connection	Connector - industrial M23 servo motor side Free end servo drive side
Net Weight	5.05 lb(US) (2.29 kg)

Ordering and shipping details

Category	US1PC5118263
Discount Schedule	PC51
GTIN	3389119207317
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Nbr. of units in pkg.	1
Package 1 Height	2.36 in (6.000 cm)
Package 1 Width	15.75 in (40.000 cm)
Package 1 Length	15.75 in (40.000 cm)
Package weight(Lbs)	5.066 lb(US) (2.298 kg)
Unit Type of Package 2	S06
Number of Units in Package 2	30
Package 2 Height	29.53 in (75.000 cm)
Package 2 Width	23.62 in (60.000 cm)
Package 2 Length	31.50 in (80.000 cm)
Package 2 Weight	184.086 lb(US) (83.500 kg)

Contractual warranty

Warranty	18 months
-----------------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 634

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

PVC free Yes

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No