


Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:

XCKL10011H7



Telemecanique Sensors
 1875 Founders Drive
 Dayton, OH 45420-4017
 Customer Care Center : 1-800-435-2121
 Web : www.tesensors.com

Technical Information:

Terminal Type: Screw Clamp
 Enclosure Rating: NEMA 1/2/4/6/6P/12/13; IP66
 Approvals: UL # E164353 CCN NKCR - CSA # LR44087 Class 3211-03 - CE Marked
 Weight: 0.380 kg (0.840 lb)
 Conforming to Standards:
 RoHS: No
 Operating Temperature Range: -13 to 158 ° F
 Shock Resistance: 50G
 Vibration Resistance: 25G
 Max. Actuation Speed : 1.5 m/s
 Repeat Accuracy:
 Operating Torque/Force: 14.2 Inch-Ounces (0.10Nm)

Specification:

Description: XCKL Limit Switch for actuation from left or right
 Body Style/Type Description: IEC OsiSense Limit Switches XCKL Compact SemiModular 52 mm Metal Body
 Head Type: ZCKG00 Rotary CW/CCW actuation + ZCKY11 plastic roller lever
 Lever Arms: ZCKY11 Thermoplastic roller lever for ZCKG00 head
 Body with Contact Type: ZCKL1H7 2-pole N.O./N.C. Snap Action
 Conduit Thread: 1/2" NPT
 Ampere Rating Continuous: 10A
 Maximum Voltage Rating: 240VAC/250VDC
 Actuation: CW and CCW
 Actuator Action: Momentary
 Lever Arm Length: 41mm
 Roller Dimension: 23mm x 5.1mm
 Roller Material: Delrin
 Contact Configuration: 1 N.O./1 N.C.
 Contact Operation: Snap Action
 Connection Type: Conduit Entrance (0.5 Inch NPT)
 Head Material: Zamak
 Positive Opening: Yes
 Cable Length: