

Product data sheet

Specifications



Universal Mounting Accessory, Harmony XV4/XV6/XVB7 Modular Tower Light, Metal L Bracket & 250mm Alu Pole

XVZ250T

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Accessory
Accessory / Separate Part Type	L bracket alu Ø 25mm pole 250mm
Product Compatibility	XVB7..... XV6..... XV4.....
Material	Aluminium and steel
Product Weight	0.840 lb(US) (0.381 kg)

Complementary

Height	11.7 in (298 mm)
cable entry	Bottom entry
Color	Silver

Environment

IP degree of protection	IP54 horizontal surface IP23 vertical surface
Environmental Type ratings	Type 1

Ordering and shipping details

Category	US100XV22612
Discount Schedule	00XV
GTIN	3606487130574
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.05 in (5.2 cm)
Package 1 Width	3.58 in (9.1 cm)
Package 1 Length	10.67 in (27.1 cm)
Package 1 Weight	15.1 oz (429 g)
Unit Type of Package 2	S03

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 2	20
Package 2 Height	11.81 in (30 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	20.90 lb(US) (9.48 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	160
Package 3 Height	28.35 in (72 cm)
Package 3 Width	23.62 in (60 cm)
Package 3 Length	31.50 in (80 cm)
Package 3 Weight	167.20 lb(US) (75.84 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	5	
Environmental Disclosure	Product Environmental Profile	

Use Better

Materials and Substances		
Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
REACH Regulation	REACH Declaration	

Use Again

Repack and remanufacture		
Circularity Profile	End of Life Information	
Take-back	No	

Offer Marketing Illustration

Product benefits / Features

Features

Harmony XVB7



Sustainability: high brightness with low power consumption realized via energy efficient LED



Elevated design with a modern twist to enhance machine aesthetic



Modular design for adaptability, ease of maintenance and low inventory





Wide base variety with the option to be connected via USB & IO-link base



Adjustable and customizable sounder with maximum sound pressure of up to 102dB

Offer Marketing Illustration

Product benefits / Features

Technical Benefits
Harmony XVB7

Conformity with IEC, CUL and CCC standards, as well as CE marking

Up to IP66 and type 4X protection ratings

High shock and vibration resistance up to 6g



Energy efficient LED with operating life up to 50,000 hours

Save up to 75% wiring time with M12 connection and push-in terminal

High brightness level with illuminance up to 3000cd/m2

Image of product / Alternate images

Alternative





