

# Product data sheet

Specifications



Head for pilot light, Harmony XAC,  
for incandescent bulb, plastic, yellow  
cap, 22mm

ZA2BV05

**Product availability: Non-Stock - Not normally stocked in  
distribution facility**

## Main

Range of Product	Harmony
Product or Component Type	Head for pilot light
Product Specific Application	For incandescent bulb
Cap/operator or lens colour	Yellow

## Complementary

Mechanical durability	1000000 cycles
Net Weight	0.033 lb(US) (0.015 kg)
Compatibility code	ZA2B

## Environment

Standards	IEC 60947-5-1 CSA C22.2 No 14
Protective treatment	TH
Ambient Air Temperature for Operation	-13...131 °F (-25...55 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Vibration resistance	15 gn (f= 10...500 Hz) conforming to IEC 60068-2-6
Shock resistance	100 gn IEC 60068-2-27
Electrical shock protection class	Class II conforming to IEC 61140
Overvoltage category	Class II conforming to IEC 61140
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

## Ordering and shipping details

Category	US10CS222460
Discount Schedule	0CS2
GTIN	3389110648249
Returnability	Yes
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	1.4 in (3.6 cm)
<b>Package 1 Width</b>	2.8 in (7.2 cm)
<b>Package 1 Length</b>	3.8 in (9.7 cm)
<b>Package weight(Lbs)</b>	0.5 oz (15.0 g)
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	1.6 in (4.0 cm)
<b>Package 2 Width</b>	6.7 in (17.0 cm)
<b>Package 2 Length</b>	6.7 in (17.0 cm)
<b>Package 2 Weight</b>	5.4 oz (152.0 g)
<b>Unit Type of Package 3</b>	S02
<b>Number of Units in Package 3</b>	100
<b>Package 3 Height</b>	5.9 in (15.0 cm)
<b>Package 3 Width</b>	11.8 in (30.0 cm)
<b>Package 3 Length</b>	15.7 in (40.0 cm)
<b>Package 3 Weight</b>	4.037 lb(US) (1.831 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 1

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

California proposition 65 **WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No