
# ZB2BY4951

legend - 30 x 40 mm - white - raise, slow



# Main Product or Component Type Device application With symbol NF E 52-124 Accessory / separate part type Accessory / separate part categor Marking accessory

### Complementary

Marking	Black raise, slow white vertical mounting)	
User Language	English	
Standards	NF E 52-124	
Net Weight	0.002 lb(US) (0.001 kg)	
Accessory / separate part destination	Pendant control station for control circuit Pendant control station for power circuit	
Product Compatibility	XACM XACB	
Type of Marking	Symbolic	
Label dimensions	30 x 40 mm	

### Ordering and shipping details

Category	US10CS222466	
Discount Schedule	0CS2	
GTIN	3389110615173	
Returnability	No	
Country of origin	FR	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.039 in (0.100 cm)
Package 1 Width	1.181 in (3.000 cm)
Package 1 Length	1.575 in (4.000 cm)
Package 1 Weight	0.071 oz (2.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	0.787 in (2.000 cm)
Package 2 Width	0.787 in (2.000 cm)
Package 2 Length	2.362 in (6.000 cm)
Package 2 Weight	0.353 oz (10.000 g)
Unit Type of Package 3	S01
Number of Units in Package 3	800
Package 3 Height	5.906 in (15.000 cm)
Package 3 Width	5.906 in (15.000 cm)

Package 3 Length	15.748 in (40.000 cm)	
Package 3 Weight	32.804 oz (930.000 g)	
Offer Sustainability		
California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEN RoHS  Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☐ China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Circularity Profile	No need of specific recycling operations	
Contractual warranty		
Warranty	18 months	