

Product data sheet

Specifications



Plain cap, Harmony XB5, Harmony XB4, black, for flush mounted push button

ZBAF2

Product availability: Stock - Normally stocked in distribution facility

Main

Accessory / separate part category	Marking accessory
Accessory / Separate Part Type	Blank push-button cap
Product or Component Type	Antimicrobial plain cap
Product Compatibility	ZB4FA0 ZB5FA0
Accessory / separate part destination	Push-button head
Cap/operator or lens colour	Black
Shape of signaling unit head	Round
Quantity per Set	Set of 1
Sale per indivisible quantity	10
Net Weight	0.002 lb(US) (0.001 kg)

Complementary

Range Compatibility	Harmony XAL Harmony XB5 Harmony XB4
Operator profile	Flush
Main group	Selector switch Push-button

Environment

Standards	ISO 21702 ISO 22196:2011
-----------	-----------------------------

Ordering and shipping details

Category	US10CS222467
Discount Schedule	0CS2
GTIN	3606481340689
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	0.787 in (2.000 cm)
Package 1 Width	0.984 in (2.500 cm)
Package 1 Length	0.984 in (2.500 cm)
Package weight(Lbs)	0.071 oz (2.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	1.575 in (4.000 cm)
Package 2 Width	2.165 in (5.500 cm)
Package 2 Length	2.165 in (5.500 cm)
Package 2 Weight	0.847 oz (24.000 g)
Unit Type of Package 3	S01
Number of Units in Package 3	200
Package 3 Height	5.906 in (15.000 cm)
Package 3 Width	5.906 in (15.000 cm)
Package 3 Length	15.748 in (40.000 cm)
Package 3 Weight	23.986 oz (680.000 g)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 1

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XB5

Conformity with IEC, UL, CSA, CCC EAC, and JIS standards, as well as CE marking and marine approvals

Up to IP66, 67, 69, 69K, and type 4X protection ratings

High vibration resistance with shake-proof terminal screws



Operating temperature from -40°C to 70°C

Shock protection level up to IK06

Secure switching of inductive or heavy DC loads directly – 100 000 operations at 10A, 24V dc

Offer Marketing Illustration

Product benefits / Features

Features Harmony XB5



- 

Quick and easy assembly and disassembly
- 

Excellent mechanical connection with operator head
- 

Various types of connection: screw clamp, connector, Faston connector, spring terminal, or printed circuit board
- 

Large set of accessories to customize your panels
- 

Robustness to withstand harsh environments

Image of product / Alternate images

Alternative





