

Catalog Number: HS6-1-12.000
Product ID: 7TAA017110R0014
UPC Number: 78621071069
Status: Active



Heat Shrink Tubing, Cable Range #6-#1 AWG, Black, 12 inches, 100 Pieces

Actual

North American Specifications (UNSPSC)

UNSPSC	39121723 Heat shrinkable tube
IGCC	5073 Heat shrinkable tube
Brand Name	Shrink-Kon
Type	Heat Shrink Tubing
Shrink Ratio	3:1
Voltage Rating	600V
Length	12 in ; 304.8 mm
Dielectric Strength	500 V/Mil (20kV/mm)
Volume Resistivity	1016 ohm-cm
Continuous Operating Temperature	-67 Degrees F (-55C) to 230 Degrees F (110 C)
Minimum Shrink Temperature	248 Degrees F (120 C)
Water Absorption	0.10%
Color	Black

European Specifications (ETIM)

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thick-walled
Shrink rate	3:1
Inner diameter before heat-shrink	19.05mm
Inner diameter after heat-shrink	6.096mm
Nominal diameter inch	3/4 inch
Wall thickness after shrinking	3.048mm
Length	0.3048m
Operation temperature	-55-+110°C
Colour	Black
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	N

Packaging

Outer Quantity	100
Outer Dimensions (inches)	13x6x13
Weight Uom	6.56 lbs. per 100

Documents / Support Tools

Safety Data Sheet (SDS) Global	SDS-00046-TB2
--------------------------------	---------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com