

Figure similar

MLFB-Ordering data

1FK2105-6AF00-1SA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Basic motor data		Mechanical data	
Motor type	Permanent-magnet synchronous motor, Natural cooling, IP64	Design acc. to Code I	IM B5 (IM V1, IM V3)
Motor type	High Dynamic	Vibration severity grade	Grade A
Static torque	8.00 Nm	Shaft height	52
Static current	6.7 A	Flange size (AB)	105 mm
Maximum torque	24.00 Nm	Centering ring (N)	95 mm
Maximum current	24.0 A	Hole circle (M)	115 mm
Maximum speed	6000 rpm	Screw-on hole (S)	9.0 mm
Rotor moment of inertia	2.650 kgcm <sup>2</sup>	Overall length (LB)	201 mm
Weight	7.7 kg	Diameter of shaft (D)	19 mm
		Length of shaft (E)	40 mm
		Length of flange diagonal (P)	135 mm
		Shaft extension	Fitted key

### Rated data

SINAMICS S210, 3AC 400V

Rated speed	3000 rpm
Rated torque	6.60 Nm
Rated current	5.6 A
Rated power	2.10 kW

### Encoder system

Encoder system	Encoder AS22DQC: Absolute encoder single turn 22 bit
----------------	--

### Motor connection

Connection type	OCC for S210
Connector size	M17




Figure similar