

SECTION FUS-NH 3x 400 A SANS COMM

Model	
product designation	switch disconnecter with fuses
design of the product	for NH 2
fuse system	NH 2
Supply voltage	
operating voltage at DC rated value	220 V
Protection class	
protection class IP	IP00
Main circuit	
operational current rated value	400 A
suitability for use safety switch	Yes
Connections	
type of electrical connection for main current circuit	BUSBAR CONNECTION
Mechanical Design	
height	230 mm
width	280 mm
depth	140.5 mm
fastening method	Surface mounting and installation
net weight	7 kg
Environmental conditions	
ambient temperature during operation	
• minimum	-20 °C
• maximum	45 °C
ambient temperature during storage minimum	-25 °C
Approvals Certificates	
General Product Approval	



[Confirmation](#)



General Product Approval

EMV

Test Certificates



[Miscellaneous](#)



[Miscellaneous](#)



[Miscellaneous](#)

Marine / Shipping

other



[Miscellaneous](#)

other

Environment



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KL7142-3AA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3KL7142-3AA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KL7142-3AA00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

9/14/2021 

