



SENTRON, Switch disconnecter 3LD, emergency switching-off switch, 3- pole, Iu: 32 A, operating power / at AC-23 A 400 V: 11.5 kW, molded-plastic encapsulation for inch cable gland, 2 NO, rotary operating mechanism, red/yellow

| Model | |
|---|--|
| product brand name | SENTRON |
| product designation | Switch disconnecter |
| design of the product | EMERGENCY-STOP switch |
| display version for switch position indicator manual operation | 1 ON - 0 OFF |
| type of switch | Molded-plastic enclosure for inch threaded joint |
| design of the actuating element | Short rotary knob |
| color of the actuating element | red |
| design of handle | rotary operating mechanism, red/yellow |
| type of the driving mechanism motor drive | No |
| General technical data | |
| number of poles | 3 |
| number of poles note | PE |
| size of switch disconnecter | 2 |
| mechanical service life (operating cycles) typical | 100 000 |
| electrical endurance (operating cycles) | |
| • at AC-23 A at 690 V | 6 000 |
| operating frequency maximum | 50 1/h |
| degree of pollution | 3 |
| Voltage | |
| insulation voltage rated value | 690 V |
| surge voltage resistance rated value | 6 kV |
| operating voltage | |
| • at AC rated value | 690 V |
| operating frequency rated value | |
| • minimum | 50 Hz |
| • maximum | 60 Hz |
| Protection class | |
| protection class IP | IP65 |
| degree of protection NEMA rating | 1, 4X, 12 |
| protection class IP on the front | IP65 |
| Dissipation | |
| power loss [W] for rated value of the current at AC in hot operating state per pole | 1.8 W |
| Main circuit | |
| operational current | |
| • at AC-21 at 690 V rated value | 32 A |
| • at AC-21 A at 240 V rated value | 32 A |
| • at AC-21 A at 400 V rated value | 32 A |

| | |
|--|--|
| <ul style="list-style-type: none"> • at AC-21 A at 440 V rated value • at AC-23 A at 400 V rated value | 32 A 22 A |
| operating power | |
| <ul style="list-style-type: none"> • at AC-23 A at 240 V rated value • at AC-23 A at 400 V rated value • at AC-23 A at 440 V rated value • at AC-23 A at 690 V rated value • at AC-3 at 240 V rated value • at AC-3 at 400 V rated value • at AC-3 at 690 V rated value | 6 kW 12 kW 11.5 kW 12 kW 5.5 kW 10 kW 9.5 kW |
| Auxiliary circuit | |
| number of CO contacts for auxiliary contacts | 0 |
| number of NC contacts for auxiliary contacts | 0 |
| number of NO contacts for auxiliary contacts | 2 |
| operating voltage of auxiliary contacts at AC maximum | 500 V |
| continuous current of the auxiliary contact rated value | 10 A |
| insulation voltage of the auxiliary switch rated value | 500 V |
| Suitability | |
| suitability for use main switch | Yes |
| suitability for use switch disconnecter | Yes |
| suitability for use EMERGENCY OFF switch | Yes |
| suitability for use safety switch | Yes |
| suitability for use maintenance/repair switch | Yes |
| Product details | |
| product feature can be locked into OFF position | Yes |
| Accessories | |
| product extension optional | |
| <ul style="list-style-type: none"> • motor drive • voltage trigger | No No |
| number of connectable NC contacts for auxiliary contacts attachable maximum | 2 |
| number of connectable NO contacts for auxiliary contacts attachable maximum | 3 |
| number of connectable CO contacts for auxiliary contacts attachable maximum | 0 |
| number of bracket locks maximum | 3 |
| hasp thickness of the bracket locks | 4 ... 8 mm |
| Short circuit | |
| conditional short-circuit current with line-side fuse protection | |
| <ul style="list-style-type: none"> • at 690 V by gG fuse rated value | 50 kA |
| let-through current with closed switch | |
| <ul style="list-style-type: none"> • at 240 V for combination switch + gG fuse maximum • at 440 V for combination switch + gG fuse maximum • at 690 V for combination switch + gG fuse maximum permissible | 4.5 kA 4.5 kA 5 kA |
| I²t value with closed switch | |
| <ul style="list-style-type: none"> • at 240 V for combination switch + gG fuse maximum • at 440 V for combination switch + gG fuse maximum • at 690 V for combination switch + gG fuse maximum | 9 kA ² .s 9 kA ² .s 9 kA ² .s |
| design of the fuse link | |
| <ul style="list-style-type: none"> • for short-circuit protection of the main circuit required • for short-circuit protection of the auxiliary switch required | fuse gL/gG: 40 A fuse gL/gG: 10 A |
| operational current of upstream fuse rated value | 40 A |
| according UL | |
| operational current at AC according to UL 508/UL 60947-4-1 rated value | 32 A |
| operating voltage at AC at 50/60 Hz according to UL 508/UL 60947-4-1 rated value | 600 V |
| active power [hp] at AC at 480 V according to UL 508/UL 60947-4-1 rated value | 20 |
| active power [hp] at AC at 600 V according to UL 508/UL 60947-4-1 rated value | 20 |

| | |
|---|------|
| short-time withstand current (SCCR) at 600 V according to UL 508/UL 60947-4-1 | 5 kA |
| continuous current of upstream fuse according to UL rated value | 80 A |
| type of fuse according to UL | RK5 |

Connections

| | |
|---|--|
| AWG number as coded connectable conductor cross section solid maximum | 8 14 |
| type of connectable conductor cross-sections for copper conductor | <ul style="list-style-type: none"> solid: 1x (1,5...16mm²) finely stranded with core end processing: 1x (1,5...10mm²) stranded: 1x (1,5...16mm²) |
| type of connectable conductor cross-sections for auxiliary contacts | <ul style="list-style-type: none"> solid: lateral auxiliary switch 2x (0,75 ... 2,5mm²), 1x 4mm²; front auxiliary switch 1x (0,75 ... 2,5mm²) finely stranded with core end processing: lateral auxiliary switch 2x (0,75 ... 1,5mm²), 1x 2,5mm²; front auxiliary switch 1x 2,5mm² stranded: lateral auxiliary switch 2x (0,75 ... 2,5mm²), 1x 4mm²; front auxiliary switch 1x (0,75 ... 2,5mm²) |
| type of electrical connection | <ul style="list-style-type: none"> for main current circuit: box terminal for auxiliary contacts: connection terminals |

Mechanical Design

| | |
|------------------|---|
| height | 164 mm |
| width | 100 mm |
| depth | 118 mm |
| type of device | fixed mounting |
| fastening method | Complete unit in enclosure |
| fastening method | <ul style="list-style-type: none"> 4-hole front mounting: No front mounting with central attachment: Yes rail mounting: No |

| | |
|------------|-------|
| Net Weight | 436 g |
|------------|-------|

Environmental conditions

| | |
|--------------------------------------|---|
| ambient temperature during operation | <ul style="list-style-type: none"> minimum: -25 °C maximum: 55 °C |
| ambient temperature during storage | <ul style="list-style-type: none"> minimum: -25 °C maximum: 55 °C |

Approvals Certificates

General Product Approval



| | | | |
|--------------------------|-------------------|----------------------|-------|
| General Product Approval | Test Certificates | Maritime application | other |
|--------------------------|-------------------|----------------------|-------|

[Miscellaneous](#)




[Miscellaneous](#)



[Confirmation](#)

Environment

[Environmental Con-](#) [Environmental Con-](#)

Further information**Information on the packaging**<https://support.industry.siemens.com/cs/ww/en/view/109813875>**Information for data generation and storage**<https://support.industry.siemens.com/cs/ww/en/view/109995012>**Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=3LD2264-1TS53-0US2>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/3LD2264-1TS53-0US2>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mifb=3LD2264-1TS53-0US2**CAX-Online-Generator**<http://www.siemens.com/cax>**Tender specifications**<http://www.siemens.com/specifications>

last modified:

5/24/2025

