

Data sheet

3NE3231



Figure similar

SITOR fuse link, with slotted blade contacts, NH1, In: 350 A, aR, Un AC: 1000 V, front indicator

Model	
product brand name	SETRON
product designation	SITOR fuse link
design of the product	With slotted blade contacts
design of an identification indicator	front indicator
design of the switching contact	with slotted blade contacts for M10 screw fixing. mounting dimension: 110 mm. or for installation in LV HRC fuse bases or switch disconnectors
design of the fuse link	SITOR, LV HRC design
General technical data	
size of fuse system according to EN 60269-1	NH1
operating class of the fuse link	aR
varying load factor (WL)	0.9
type of voltage of the operating voltage	AC
operating voltage at AC according to UL rated value	1 000 V
Supply voltage	
supply voltage at AC	1 000 V
Breaking Capacity	
switching capacity current according to IEC 60947-2 rated value	100 kA
Dissipation	
power loss [W]	75 W
power loss [W] - for rated value of the current at AC in hot operating state per pole - maximum	75 W 75 W
Product details	
product description	with blade contacts, silver-plated
accessories included	no
Mechanical Design	
mounting position	Any, preferably vertical
net weight	596 g
Environmental conditions	
ambient temperature during operation - minimum - maximum	-20 °C 50 °C
environmental category	-20 to +50 at 95% relative humidity
Approvals Certificates	
General Product Approval	

