

AS-Interface accessory IP68 T-distributor U_Asi and Uaux for round cable 1 x M12 connector, 2 x M12 socket



General technical data		
Type of device		AS-Interface accessories
design of the product		M12-T distribution board
Function		T distribution M12
Connections/ Terminals		
type of electrical connection		M12
AS interface		
• Connection		1 x M12 connector / 2 x M12 box
Inputs		
Inputs socket assignment		1 = AS-i "+" 2 = Uaux "-" 3=AS-i "-" 4 = Uaux "+"
Mechanical data		
Type of mounting		screw fixing
Contacts Load rating max	A	4
Ambient conditions		
ambient temperature	°C	-25 ... +85
ambient temperature during storage	°C	-25 ... +85
degree of protection		IP68
Certificates/ approvals		
General Product Approval	EMV	Maritime application other



[Confirmation](#)

Environment

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1901-1TR00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1901-1TR00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1901-1TR00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1901-1TR00&lang=en

last modified:

4/1/2025 