



Withdrawable drive for contactors 3RT105, 3RT145 AC (50...60 Hz) / DC operation, 96 ... 127 V Operating mechanism: electronic with PLC input 24 V DC Spring-type terminal

product brand name	SIRIUS		
product category	Solenoid coils		
product designation	Changeover operating mechanism		
product type designation	3RT19		
General technical data			
Substance Prohibittance (Date)	05/01/2012		
SVHC substance name	Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol - 79-94-7 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol - 119-47-1 Perfluorobutane sulfonic acid (PFBS) and its salts - -		
Weight	0.56 kg		
type of voltage of the control supply voltage	AC/DC		
control supply voltage 1 at AC			
• at 50 Hz	96 ... 127 V		
• at 60 Hz	96 ... 127 V		
control supply voltage 2 at AC			
• at 50 Hz rated value	127 V		
• at 60 Hz rated value	127 V		
control supply voltage 1 at DC	96 ... 127 V		
control supply voltage 2 at DC rated value	127 V		
apparent pick-up power of magnet coil at AC			
• at 50 Hz	280 VA		
• at 60 Hz	280 VA		
inductive power factor with closing power of the coil			
• at 50 Hz	0.8		
• at 60 Hz	0.8		
apparent holding power of magnet coil at AC			
• at 50 Hz	4.4 VA		
• at 60 Hz	4.4 VA		
inductive power factor with the holding power of the coil			
• at 50 Hz	0.5		
• at 60 Hz	0.5		
Approvals Certificates			
General Product Approval		EMV	Test Certificates



[Type Test Certificates/Test Report](#)

