

Siemens  
EcoTech



Circuit breaker size S00 for motor protection, CLASS 10 with overload relay function A-release 5.5...8 A N-release 104 A screw terminal Standard switching capacity



|                                                                 |                                                   |
|-----------------------------------------------------------------|---------------------------------------------------|
| product brand name                                              | SIRIUS                                            |
| product designation                                             | Circuit breaker                                   |
| design of the product                                           | For motor protection with overload relay function |
| product type designation                                        | 3RV2                                              |
| General technical data                                          |                                                   |
| size of the circuit-breaker                                     | S00                                               |
| size of contactor can be combined company-specific              | S00, S0                                           |
| product extension auxiliary switch                              | Yes                                               |
| power loss [W] for rated value of the current                   |                                                   |
| • at AC in hot operating state                                  | 9.25 W                                            |
| • at AC in hot operating state per pole                         | 3.1 W                                             |
| insulation voltage with degree of pollution 3 at AC rated value | 690 V                                             |
| surge voltage resistance rated value                            | 6 kV                                              |
| shock resistance according to IEC 60068-2-27                    | 25g / 11 ms                                       |
| mechanical service life (operating cycles)                      |                                                   |
| • of the main contacts typical                                  | 100 000                                           |
| • of auxiliary contacts typical                                 | 100 000                                           |
| electrical endurance (operating cycles) typical                 | 100 000                                           |
| reference code according to IEC 81346-2                         | Q                                                 |
| Substance Prohibitance (Date)                                   | 10/01/2009                                        |
| Weight                                                          | 0.432 kg                                          |
| Ambient conditions                                              |                                                   |
| installation altitude at height above sea level maximum         | 2 000 m                                           |
| ambient temperature                                             |                                                   |
| • during operation                                              | -20 ... +60 °C                                    |
| • during storage                                                | -50 ... +80 °C                                    |
| • during transport                                              | -50 ... +80 °C                                    |
| relative humidity during operation                              | 10 ... 95 %                                       |
| Environmental footprint                                         |                                                   |
| Environmental Product Declaration (EPD)                         | Yes                                               |
| global warming potential [CO2 eq] total                         | 74.698 kg                                         |
| global warming potential [CO2 eq] during manufacturing          | 1.98 kg                                           |
| global warming potential [CO2 eq] during sales                  | 0.134 kg                                          |
| global warming potential [CO2 eq] during operation              | 72.7 kg                                           |
| global warming potential [CO2 eq] after end of life             | -0.116 kg                                         |
| Siemens Eco Profile (SEP)                                       | Siemens EcoTech                                   |
| Main circuit                                                    |                                                   |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                          |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| number of poles for main current circuit                                                                                                                                                                                                                                                                                                                                                                                                            | 3                                                                        |
| adjustable current response value current of the current-dependent overload release                                                                                                                                                                                                                                                                                                                                                                 | 5.5 ... 8 A                                                              |
| type of voltage for main current circuit                                                                                                                                                                                                                                                                                                                                                                                                            | AC                                                                       |
| operating voltage <ul style="list-style-type: none"> <li>• rated value</li> <li>• at AC-3 rated value maximum</li> <li>• at AC-3e rated value maximum</li> </ul>                                                                                                                                                                                                                                                                                    | 20 ... 690 V<br>690 V<br>690 V                                           |
| operating frequency rated value                                                                                                                                                                                                                                                                                                                                                                                                                     | 50 ... 60 Hz                                                             |
| operational current rated value                                                                                                                                                                                                                                                                                                                                                                                                                     | 8 A                                                                      |
| operational current <ul style="list-style-type: none"> <li>• at AC-3 at 400 V rated value</li> <li>• at AC-3e at 400 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                       | 8 A<br>8 A                                                               |
| operating power <ul style="list-style-type: none"> <li>• at AC-3 <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> <li>• at AC-3e <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul> | 1.5 kW<br>3 kW<br>4 kW<br>5.5 kW<br><br>1.5 kW<br>3 kW<br>4 kW<br>5.5 kW |
| operating frequency <ul style="list-style-type: none"> <li>• at AC-3 maximum</li> <li>• at AC-3e maximum</li> </ul>                                                                                                                                                                                                                                                                                                                                 | 15 1/h<br>15 1/h                                                         |
| <b>Auxiliary circuit</b>                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                          |
| design of the auxiliary switch                                                                                                                                                                                                                                                                                                                                                                                                                      | laterally                                                                |
| type of voltage for auxiliary and control circuit                                                                                                                                                                                                                                                                                                                                                                                                   | AC/DC                                                                    |
| number of NC contacts for auxiliary contacts                                                                                                                                                                                                                                                                                                                                                                                                        | 0                                                                        |
| number of NO contacts for auxiliary contacts                                                                                                                                                                                                                                                                                                                                                                                                        | 0                                                                        |
| number of CO contacts for auxiliary contacts                                                                                                                                                                                                                                                                                                                                                                                                        | 0                                                                        |
| operational current of auxiliary contacts at AC-15 <ul style="list-style-type: none"> <li>• at 24 V</li> <li>• at 230 V</li> </ul>                                                                                                                                                                                                                                                                                                                  | 1.5 A<br>1.5 A                                                           |
| operational current of auxiliary contacts at DC-13 <ul style="list-style-type: none"> <li>• at 24 V</li> </ul>                                                                                                                                                                                                                                                                                                                                      | 1 A                                                                      |
| <b>Protective and monitoring functions</b>                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                          |
| product function <ul style="list-style-type: none"> <li>• ground fault detection</li> <li>• phase failure detection</li> </ul>                                                                                                                                                                                                                                                                                                                      | No<br>Yes                                                                |
| trip class                                                                                                                                                                                                                                                                                                                                                                                                                                          | CLASS 10                                                                 |
| design of the overload release                                                                                                                                                                                                                                                                                                                                                                                                                      | thermal                                                                  |
| maximum short-circuit current breaking capacity (I <sub>cu</sub> ) <ul style="list-style-type: none"> <li>• at AC at 240 V rated value</li> <li>• at AC at 400 V rated value</li> <li>• at AC at 500 V rated value</li> <li>• at AC at 690 V rated value</li> </ul>                                                                                                                                                                                 | 100 kA<br>100 kA<br>42 kA<br>6 kA                                        |
| operating short-circuit current breaking capacity (I <sub>cs</sub> ) at AC <ul style="list-style-type: none"> <li>• at 240 V rated value</li> <li>• at 400 V rated value</li> <li>• at 500 V rated value</li> <li>• at 690 V rated value</li> </ul>                                                                                                                                                                                                 | 100 kA<br>100 kA<br>42 kA<br>4 kA                                        |
| response value current of instantaneous short-circuit trip unit                                                                                                                                                                                                                                                                                                                                                                                     | 104 A                                                                    |
| <b>UL/CSA ratings</b>                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                          |
| full-load current (FLA) for 3-phase AC motor <ul style="list-style-type: none"> <li>• at 480 V rated value</li> <li>• at 600 V rated value</li> </ul>                                                                                                                                                                                                                                                                                               | 8 A<br>8 A                                                               |
| yielded mechanical performance [hp] <ul style="list-style-type: none"> <li>• for single-phase AC motor</li> </ul>                                                                                                                                                                                                                                                                                                                                   |                                                                          |

|                                                                                                |                                                                          |
|------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| — at 110/120 V rated value                                                                     | 0.33 hp                                                                  |
| — at 230 V rated value                                                                         | 1 hp                                                                     |
| • for 3-phase AC motor                                                                         |                                                                          |
| — at 200/208 V rated value                                                                     | 2 hp                                                                     |
| — at 220/230 V rated value                                                                     | 2 hp                                                                     |
| — at 460/480 V rated value                                                                     | 5 hp                                                                     |
| — at 575/600 V rated value                                                                     | 5 hp                                                                     |
| <b>contact rating of auxiliary contacts according to UL</b>                                    | C600 / R300                                                              |
| <b>Short-circuit protection</b>                                                                |                                                                          |
| <b>product function short circuit protection</b>                                               | Yes                                                                      |
| <b>design of the short-circuit trip</b>                                                        | magnetic                                                                 |
| <b>design of the fuse link</b>                                                                 |                                                                          |
| • for short-circuit protection of the auxiliary switch required                                | fuse gL/gG: 6 A, quick: 10 A                                             |
| <b>design of the fuse link for IT network for short-circuit protection of the main circuit</b> |                                                                          |
| • at 400 V                                                                                     | gL/gG 50 A                                                               |
| • at 500 V                                                                                     | gL/gG 40 A                                                               |
| • at 690 V                                                                                     | gL/gG 35 A                                                               |
| <b>Installation/ mounting/ dimensions</b>                                                      |                                                                          |
| <b>mounting position</b>                                                                       | any                                                                      |
| <b>fastening method</b>                                                                        | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715 |
| <b>height</b>                                                                                  | 97 mm                                                                    |
| <b>width</b>                                                                                   | 65 mm                                                                    |
| <b>depth</b>                                                                                   | 97 mm                                                                    |
| <b>required spacing</b>                                                                        |                                                                          |
| • with side-by-side mounting at the side                                                       | 0 mm                                                                     |
| • for grounded parts at 400 V                                                                  |                                                                          |
| — downwards                                                                                    | 30 mm                                                                    |
| — upwards                                                                                      | 30 mm                                                                    |
| — at the side                                                                                  | 9 mm                                                                     |
| • for live parts at 400 V                                                                      |                                                                          |
| — downwards                                                                                    | 30 mm                                                                    |
| — upwards                                                                                      | 30 mm                                                                    |
| — at the side                                                                                  | 9 mm                                                                     |
| • for grounded parts at 500 V                                                                  |                                                                          |
| — downwards                                                                                    | 30 mm                                                                    |
| — upwards                                                                                      | 30 mm                                                                    |
| — at the side                                                                                  | 9 mm                                                                     |
| • for live parts at 500 V                                                                      |                                                                          |
| — downwards                                                                                    | 30 mm                                                                    |
| — upwards                                                                                      | 30 mm                                                                    |
| — at the side                                                                                  | 9 mm                                                                     |
| • for grounded parts at 690 V                                                                  |                                                                          |
| — downwards                                                                                    | 50 mm                                                                    |
| — upwards                                                                                      | 50 mm                                                                    |
| — backwards                                                                                    | 0 mm                                                                     |
| — at the side                                                                                  | 30 mm                                                                    |
| — forwards                                                                                     | 0 mm                                                                     |
| • for live parts at 690 V                                                                      |                                                                          |
| — downwards                                                                                    | 50 mm                                                                    |
| — upwards                                                                                      | 50 mm                                                                    |
| — backwards                                                                                    | 0 mm                                                                     |
| — at the side                                                                                  | 30 mm                                                                    |
| — forwards                                                                                     | 0 mm                                                                     |
| <b>Connections/ Terminals</b>                                                                  |                                                                          |
| <b>type of electrical connection</b>                                                           |                                                                          |
| • for main current circuit                                                                     | screw-type terminals                                                     |
| • for auxiliary and control circuit                                                            | screw-type terminals                                                     |
| <b>arrangement of electrical connectors for main current circuit</b>                           | Top and bottom                                                           |
| <b>type of connectable conductor cross-sections</b>                                            |                                                                          |

|                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• for AWG cables for main contacts</li> </ul>                                                               | 2x (0,75 ... 2,5 mm <sup>2</sup> ), 2x 4 mm <sup>2</sup><br>2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )<br>2x (18 ... 14), 2x 12                       |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• for AWG cables for auxiliary contacts</li> </ul> | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )<br>2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )<br>2x (20 ... 16), 2x (18 ... 14) |
| <b>tightening torque</b> <ul style="list-style-type: none"> <li>• for main contacts with screw-type terminals</li> <li>• for auxiliary contacts with screw-type terminals</li> </ul>                                                                                                                       | 0.8 ... 1.2 N·m<br>0.8 ... 1.2 N·m                                                                                                                                               |
| <b>design of screwdriver shaft</b>                                                                                                                                                                                                                                                                         | Diameter 5 to 6 mm                                                                                                                                                               |
| <b>size of the screwdriver tip</b>                                                                                                                                                                                                                                                                         | Pozidriv size 2                                                                                                                                                                  |
| <b>design of the thread of the connection screw</b> <ul style="list-style-type: none"> <li>• for main contacts</li> <li>• of the auxiliary and control contacts</li> </ul>                                                                                                                                 | M3<br>M3                                                                                                                                                                         |

#### Safety related data

|                                                                                                                                                                                               |              |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| product function suitable for safety function                                                                                                                                                 | Yes          |
| <b>suitability for use</b> <ul style="list-style-type: none"> <li>• safety-related switching on</li> <li>• safety-related switching OFF</li> </ul>                                            | No<br>Yes    |
| <b>service life maximum</b>                                                                                                                                                                   | 10 a         |
| <b>test wear-related service life necessary</b>                                                                                                                                               | Yes          |
| <b>proportion of dangerous failures</b> <ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920</li> <li>• with high demand rate according to SN 31920</li> </ul> | 40 %<br>50 % |
| <b>B10 value with high demand rate according to SN 31920</b>                                                                                                                                  | 5 000        |
| <b>failure rate [FIT] with low demand rate according to SN 31920</b>                                                                                                                          | 50 FIT       |

#### ISO 13849

|                                                            |     |
|------------------------------------------------------------|-----|
| <b>device type according to ISO 13849-1</b>                | 3   |
| <b>overdimensioning according to ISO 13849-2 necessary</b> | Yes |

#### IEC 61508

|                                                                                                                                    |        |
|------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>safety device type according to IEC 61508-2</b>                                                                                 | Type A |
| <b>T1 value</b> <ul style="list-style-type: none"> <li>• for proof test interval or service life according to IEC 61508</li> </ul> | 10 a   |

#### Electrical Safety

|                                                                |                                                  |
|----------------------------------------------------------------|--------------------------------------------------|
| <b>protection class IP on the front according to IEC 60529</b> | IP20                                             |
| <b>touch protection on the front according to IEC 60529</b>    | finger-safe, for vertical contact from the front |

#### Display

|                                      |        |
|--------------------------------------|--------|
| display version for switching status | Handle |
|--------------------------------------|--------|

#### Approvals Certificates

##### General Product Approval



KC



|                          |                   |                      |
|--------------------------|-------------------|----------------------|
| General Product Approval | Test Certificates | Maritime application |
|--------------------------|-------------------|----------------------|



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



|                      |       |
|----------------------|-------|
| Maritime application | other |
|----------------------|-------|



[Confirmation](#)

[Miscellaneous](#)



other

Railway

Environment



[Special Test Certificate](#)

[Confirmation](#)



[Environmental Confirmations](#)

#### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV2111-1HA10>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2111-1HA10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2111-1HA10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)



[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV2111-1HA10&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV2111-1HA10&lang=en)


Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2111-1HA10/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RV2111-1HA10&objecttype=14&gridview=view1>





## TEST

