

Surge suppressor Interference suppression diode with cable spacer 24-250 V DC for mounting to coil terminal for contactor relays 3TH4



product category	Surge suppressor
product designation	Interference suppression diode
product type designation	3TX7
suitability for use	for 3TH4
General technical data	
certificate of suitability	CE / UL / CSA
Substance Prohibitance (Date)	03/01/2017
Weight	0.014 kg
type of voltage of the control supply voltage	DC
control supply voltage at DC rated value	24 ... 250 V
design of the surge suppressor	diode
Ambient conditions	
ambient temperature	
• during operation	-25 ... +55 °C
• during storage	-40 ... +80 °C
Approvals Certificates	
General Product Approval	other



[Confirmation](#)

Environment

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7402-3A>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7402-3A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7402-3A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

last modified:

4/2/2025 